




STELLAR™ PENDANT




FIXTURE WEIGHT 20 LBS




FIXTURE WEIGHT 30 LBS



FIXTURE WEIGHT 40 LBS




FIXTURE WEIGHT 60 LBS




FIXTURE WEIGHT 70 LBS




ST1-P1AA-24-GW-BAL




FIXTURE WEIGHT 20 LBS




FIXTURE WEIGHT 30 LBS



FIXTURE WEIGHT 40 LBS



FIXTURE WEIGHT 60 LBS



FIXTURE WEIGHT 70 LBS



ST1-P1ED-24-GW-BKP

MATCHING FIXTURES



page 148



page 152



page 292



page 430



page 474

FEATURES

- The classic look of crown molding creates the stately appearance of the Stellar.
- Spun from solid, non-ferrous 0.040" thick brass, 0.040" thick copper, or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
<p>ST1 (SHALLOW DIFFUSER)</p> <p>ST2 (DEEP DIFFUSER)</p>	<b>P1AA</b> PENDANT WITH A SINGLE CENTER STEM	18	<b>GW</b> GLOSS WHITE ACRYLIC	<b>PAL</b> POLISHED ALUMINUM	<b>18"</b>	<b>120</b>	24	<b>DMA</b> ADVANCE® DIMMING BALLAST
			<b>MW</b> MATTE WHITE ACRYLIC	<b>BAL</b> BRUSHED ALUMINUM	<b>40D26</b> 4@26W QD (10989.0)	<b>277</b>		<b>DML</b> LUTRON® DIMMING BALLAST
	<b>P1AD</b> PENDANT WITH 3 VERTICAL SATELLITE STEMS AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY	24	<b>FA</b> FAUX ALABASTER ACRYLIC	<b>PBR</b> POLISHED BRASS	<b>24"</b>	<b>347</b>	32	<b>EMI</b> INTEGRAL EMERGENCY
			<b>NH</b> NATURAL HORN ACRYLIC	<b>BBR</b> BRUSHED BRASS	<b>4TT32</b> 4@32W TT (9530.0)	<b>4TT42</b> 4@42W TT		<b>FUS</b> FUSED
	<b>P1AH</b> PENDANT WITH 3 ANGLED STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY	31	<b>ET</b> ETRUSCAN ACRYLIC	<b>ABR</b> ANTIQUE BRASS	<b>48X39</b> 4@39W BX (8222.1)	<b>3IN150</b> 3@150W IN (13742.0)	40	<b>TLP</b> TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)
			<b>WS</b> WHITE SWIRL ACRYLIC	<b>SNK</b> SATIN NICKEL	<b>3IN150</b> 3@150W IN (13742.0)	<b>80D26</b> 8@26W QD (12189.0)		<b>6BX40</b> 6@40W BX
	<b>P1AI</b> PENDANT WITH 3 ANGLED REEDED STEMS TO COLLECTOR AND A SINGLE REEDED CENTER STEM FROM TRIM RING TO CANOPY	42			<b>PTD</b> PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	<b>6BX50</b> 6@50W BX (12186.0)	50	<b>ULD</b> UL DAMP LABEL
					<b>80D26</b> 8@26W QD (12189.0)	<b>6BX55</b> 6@55W BX		<b>TRC</b> TRIPLE CIRCUIT
	<b>P1ED</b> PENDANT WITH 3 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY	51				<b>8BX39</b> 8@39W BX (12187.0)	54	<b>DNL</b> PAR DOWN LIGHT
						<b>3IN150</b> 3@150W IN (7130.0)		<b>9BX40</b> 9@40W BX
	<b>P16H</b> PENDANT WITH 4 DRAPED CHAINS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY (INCLUDES BFL)					<b>9BX50</b> 9@50W BX (13747.0)		<b>VOL</b> "V" STYLE OVERLAY AND BOTTOM FINIAL
						<b>6IN150</b> 6@150W IN (13743.0)		<b>9BX55</b> 9@55W BX
SPECIFY CATALOG CODE					<b>12BX39</b> 12@39W BX			
					<b>12BX40</b> 12@40W BX			
					<b>12BX50</b> 12@50W BX (13748.0)			
					<b>12BX55</b> 12@55W BX			
					<b>8IN150</b> 8@150W IN (13744.0)			


PENDANT

SAMPLE CODE: ST1-P1ED-24-GW-BKP-4TT32-120-32-TLP

PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM


- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.
- Bottom finial option increases overall height by length of the finial.

- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- Par down light option available in combination with a variety of compact fluorescent reflectors.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.




BFL  
BOTTOM FINIAL


STELLAR™ PENDANT




FIXTURE WEIGHT 20 LBS




FIXTURE WEIGHT 30 LBS



FIXTURE WEIGHT 40 LBS



FIXTURE WEIGHT 60 LBS




FIXTURE WEIGHT 70 LBS




ST1-P1AD-24-WS-BNP




ST1-P1AH-24-GW-PBR




FIXTURE WEIGHT 20 LBS




FIXTURE WEIGHT 30 LBS



FIXTURE WEIGHT 40 LBS



FIXTURE WEIGHT 60 LBS



FIXTURE WEIGHT 70 LBS

MATCHING FIXTURES



page 148



page 152



page 292



page 430



page 474

FEATURES

- The classic look of crown molding creates the stately appearance of the Stellar.
- Spun from solid, non-ferrous 0.040" thick brass, 0.040" thick copper, or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
<p>ST1 (SHALLOW DIFFUSER)</p> <p>ST2 (DEEP DIFFUSER)</p>	<b>P1AA</b> PENDANT WITH A SINGLE CENTER STEM	18	<b>GW</b> GLOSS WHITE ACRYLIC	<b>PAL</b> POLISHED ALUMINUM	<b>18"</b>	<b>120</b>	24	<b>DMA</b> ADVANCE® DIMMING BALLAST
			<b>MW</b> MATTE WHITE ACRYLIC	<b>BAL</b> BRUSHED ALUMINUM	<b>40D26</b> 4@26W QD (10989.0)	<b>277</b>		
	<b>P1AD</b> PENDANT WITH 3 VERTICAL SATELLITE STEMS AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY	24	<b>FA</b> FAUX ALABASTER ACRYLIC	<b>PTR</b> PEWTER	<b>2IN100</b> 2@100W IN (7135.0)	<b>347</b>	32	<b>DML</b> LUTRON® DIMMING BALLAST
			<b>NH</b> NATURAL HORN ACRYLIC	<b>PBR</b> POLISHED BRASS	<b>4TT32</b> 4@32W TT (9530.0)			
	<b>P1AH</b> PENDANT WITH 3 ANGLED STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY	31	<b>ET</b> ETRUSCAN ACRYLIC	<b>ABR</b> ANTIQUE BRASS	<b>4TT42</b> 4@42W TT		40	<b>EMI</b> INTEGRAL EMERGENCY
			<b>WS</b> WHITE SWIRL ACRYLIC	<b>STB</b> STATUARY BRONZE	<b>4BX39</b> 4@39W BX (8222.1)			
	<b>P1AI</b> PENDANT WITH 3 ANGLED REEDED STEMS TO COLLECTOR AND A SINGLE REEDED CENTER STEM FROM TRIM RING TO CANOPY	42			<b>PTD</b> PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	<b>3IN150</b> 3@150W IN (13742.0)	50	<b>FUS</b> FUSED
						<b>80D26</b> 8@26W QD (12189.0)		
	<b>P1ED</b> PENDANT WITH 3 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY	51				<b>6BX40</b> 6@40W BX	54	<b>TLP</b> TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)
	<b>P16H</b> PENDANT WITH 4 DRAPED CHAINS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY (INCLUDES BFL)					<b>6BX55</b> 6@55W BX		<b>CIB</b> CLEAR INNER BOWL
					<b>8BX40</b> 8@40W BX		<b>ULD</b> UL DAMP LABEL	
					<b>3IN150</b> 3@150W IN (7130.0)			
					<b>8TT42</b> 8@42W TT (13749.0)		<b>DNL</b> PAR DOWN LIGHT	
					<b>9BX39</b> 9@39W BX			
					<b>9BX40</b> 9@40W BX		<b>VOL</b> "V" STYLE OVERLAY AND BOTTOM FINIAL	
					<b>9BX50</b> 9@50W BX (13747.0)			
					<b>9BX55</b> 9@55W BX		<b>OOL</b> "O" STYLE OVERLAY AND BOTTOM FINIAL	
					<b>6IN150</b> 6@150W IN (13743.0)			
					<b>51"</b>			
					<b>12BX39</b> 12@39W BX			
					<b>12BX40</b> 12@40W BX			
					<b>12BX50</b> 12@50W BX (13748.0)			
					<b>12BX55</b> 12@55W BX			
					<b>8IN150</b> 8@150W IN (13744.0)			

↓ SPECIFY CATALOG CODE

SAMPLE CODE: **ST1-P1AH-24-GW-PBR-4TT32-120-40-DMA**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM


- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.
- Bottom finial option increases overall height by length of the finial.

- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- Par down light option available in combination with a variety of compact fluorescent reflectors.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.




**BFL**  
BOTTOM FINIAL


STELLAR™ PENDANT




FIXTURE WEIGHT 20 LBS




FIXTURE WEIGHT 30 LBS



FIXTURE WEIGHT 40 LBS



FIXTURE WEIGHT 60 LBS




FIXTURE WEIGHT 70 LBS




ST2-P1AI-24-FA-STB




ST2-P1GH-24-GW-ABR




FIXTURE WEIGHT 20 LBS




FIXTURE WEIGHT 30 LBS



FIXTURE WEIGHT 40 LBS



FIXTURE WEIGHT 60 LBS



FIXTURE WEIGHT 70 LBS

MATCHING FIXTURES



page 140



page 152



page 292



page 430



page 474

FEATURES

- The classic look of crown molding creates the stately appearance of the Stellar.
- Spun from solid, non-ferrous 0.040" thick brass, 0.040" thick copper, or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS	
<p>ST1 (SHALLOW DIFFUSER)</p> <p>ST2 (DEEP DIFFUSER)</p>	<b>P1AA</b> PENDANT WITH A SINGLE CENTER STEM	18	<b>GW</b> GLOSS WHITE ACRYLIC	<b>PAL</b> POLISHED ALUMINUM	<b>18"</b>	<b>120</b>	26	<b>DMA</b> ADVANCE® DIMMING BALLAST	
			<b>MW</b> MATTE WHITE ACRYLIC	<b>BAL</b> BRUSHED ALUMINUM	<b>40D26</b> 4@26W QD (10989.0)	<b>277</b>		<b>DML</b> LUTRON® DIMMING BALLAST	
	<b>P1AD</b> PENDANT WITH 3 VERTICAL SATELLITE STEMS AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY	24	<b>FA</b> FAUX ALABASTER ACRYLIC	<b>PTR</b> PEWTER	<b>24"</b>	<b>2IN100</b> 2@100W IN (7135.0)	347	35	<b>EMI</b> INTEGRAL EMERGENCY
			<b>NH</b> NATURAL HORN ACRYLIC	<b>BBR</b> BRUSHED BRASS	<b>4TT32</b> 4@32W TT (9530.0)				<b>FUS</b> FUSED
	<b>P1AH</b> PENDANT WITH 3 ANGLED STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY	31	<b>ET</b> ETRUSCAN ACRYLIC	<b>ABR</b> ANTIQUE BRASS	<b>4TT42</b> 4@42W TT	<b>4B39</b> 4@39W BX (8222.1)	43	43	<b>TLP</b> TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)
			<b>WS</b> WHITE SWIRL ACRYLIC	<b>STB</b> STATUARY BRONZE	<b>4B39</b> 4@39W BX (8222.1)				<b>CIB</b> CLEAR INNER BOWL
	<b>P1AI</b> PENDANT WITH 3 ANGLED REEDED STEMS TO COLLECTOR AND A SINGLE REEDED CENTER STEM FROM TRIM RING TO CANOPY	42	<b>PTD</b> PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	<b>SNK</b> SATIN NICKEL	<b>3IN150</b> 3@150W IN (13742.0)	<b>31"</b>	55	55	<b>ULD</b> UL DAMP LABEL
				<b>ORB</b> OIL RUBBED BRONZE	<b>80D26</b> 8@26W QD (12189.0)				<b>TRC</b> TRIPLE CIRCUIT
	<b>P1ED</b> PENDANT WITH 3 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY	51	<b>8BX40</b> 6@40W BX	<b>8BX39</b> 8@39W BX (12187.0)	<b>3IN150</b> 3@150W IN (7130.0)	<b>42"</b>	59	59	<b>TRC</b> TRIPLE CIRCUIT
				<b>9BX39</b> 9@39W BX	<b>8TT42</b> 8@42W TT (13749.0)				<b>9BX40</b> 9@40W BX
	<b>P16H</b> PENDANT WITH 4 DRAPED CHAINS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY (INCLUDES BFL)	51	<b>9BX50</b> 9@50W BX (13747.0)	<b>9BX55</b> 9@55W BX	<b>6IN150</b> 6@150W IN (13743.0)	<b>51"</b>	59	59	<b>BFL</b> BOTTOM FINIAL (SEE BELOW)
				<b>12BX39</b> 12@39W BX	<b>12BX40</b> 12@40W BX				<b>12BX50</b> 12@50W BX (13748.0)
<input type="checkbox"/> SPECIFY CATALOG CODE		<b>12BX55</b> 12@55W BX	<b>8IN150</b> 8@150W IN (13744.0)						

SAMPLE CODE: ST2-P16H-24-GW-ABR-4TT32-120-40

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM


- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.
- Bottom finial option increases overall height by length of the finial.

- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- Par down light option available in combination with a variety of compact fluorescent reflectors.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.




BFL  
BOTTOM FINIAL


STELLAR™ PENDANT




FIXTURE WEIGHT 20 LBS




FIXTURE WEIGHT 30 LBS



FIXTURE WEIGHT 40 LBS



FIXTURE WEIGHT 60 LBS




FIXTURE WEIGHT 70 LBS




ST2-P1AA-24-GW-BMP




ST2-P1AH-24-FA-ABR




FIXTURE WEIGHT 20 LBS




FIXTURE WEIGHT 30 LBS



FIXTURE WEIGHT 40 LBS



FIXTURE WEIGHT 60 LBS



FIXTURE WEIGHT 70 LBS

MATCHING FIXTURES



page 140



page 152



page 292



page 430



page 474

FEATURES

- The classic look of crown molding creates the stately appearance of the Stellar.
- Spun from solid, non-ferrous 0.040" thick brass, 0.040" thick copper, or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS	
<p>ST1 (SHALLOW DIFFUSER)</p> <p>ST2 (DEEP DIFFUSER)</p>	<p><b>P1AA</b> PENDANT WITH A SINGLE CENTER STEM</p>	18	<p><b>GW</b> GLOSS WHITE ACRYLIC</p> <p><b>MW</b> MATTE WHITE ACRYLIC</p>	<p><b>PAL</b> POLISHED ALUMINUM</p> <p><b>BAL</b> BRUSHED ALUMINUM</p> <p><b>PTR</b> PEWTER</p>	<p><b>18"</b></p> <p><b>40D26</b> 4@26W QD (10989.0)</p> <p><b>2IN100</b> 2@100W IN (7135.0)</p>	120	26	<p><b>DMA</b> ADVANCE® DIMMING BALLAST</p> <p><b>DML</b> LUTRON® DIMMING BALLAST</p>	
	<p><b>P1AD</b> PENDANT WITH 3 VERTICAL SATELLITE STEMS AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY</p>		<p><b>FA</b> FAUX ALABASTER ACRYLIC</p> <p><b>NH</b> NATURAL HORN ACRYLIC</p> <p><b>ET</b> ETRUSCAN ACRYLIC</p>	<p><b>PBR</b> POLISHED BRASS</p> <p><b>BBR</b> BRUSHED BRASS</p> <p><b>ABR</b> ANTIQUE BRASS</p> <p><b>STB</b> STATUARY BRONZE</p> <p><b>SNK</b> SATIN NICKEL</p>	<p><b>24"</b></p> <p><b>4TT32</b> 4@32W TT (9530.0)</p> <p><b>4TT42</b> 4@42W TT</p> <p><b>4BX39</b> 4@39W BX (8222.1)</p> <p><b>3IN150</b> 3@150W IN (13742.0)</p>			347	35
	<p><b>P1AH</b> PENDANT WITH 3 ANGLED STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY</p>	31	<p><b>WS</b> WHITE SWIRL ACRYLIC</p>	<p><b>ORB</b> OIL RUBBED BRONZE</p> <p><b>PTD</b> PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p><b>31"</b></p> <p><b>80D26</b> 8@26W QD (12189.0)</p> <p><b>6BX40</b> 6@40W BX</p> <p><b>6BX50</b> 6@50W BX (12186.0)</p> <p><b>6BX55</b> 6@55W BX</p> <p><b>8BX39</b> 8@39W BX (12187.0)</p> <p><b>3IN150</b> 3@150W IN (7130.0)</p>	43	55		
	<p><b>P1AI</b> PENDANT WITH 3 ANGLED REEDED STEMS TO COLLECTOR AND A SINGLE REEDED CENTER STEM FROM TRIM RING TO CANOPY</p>		42	<p><b>P1ED</b> PENDANT WITH 3 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY</p>	<p><b>8TT42</b> 8@42W TT (13749.0)</p> <p><b>9BX39</b> 9@39W BX</p> <p><b>9BX40</b> 9@40W BX</p> <p><b>9BX50</b> 9@50W BX (13747.0)</p> <p><b>9BX55</b> 9@55W BX</p> <p><b>6IN150</b> 6@150W IN (13743.0)</p>			59	59
	<p><b>P16H</b> PENDANT WITH 4 DRAPED CHAINS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY (INCLUDES BFL)</p>	51					<p><b>51"</b></p> <p><b>12BX39</b> 12@39W BX</p> <p><b>12BX40</b> 12@40W BX</p> <p><b>12BX50</b> 12@50W BX (13748.0)</p> <p><b>12BX55</b> 12@55W BX</p> <p><b>8IN150</b> 8@150W IN (13744.0)</p>		
	<p>▾ SPECIFY CATALOG CODE</p>								

SAMPLE CODE: **ST2-P1AH-24-FA-ABR-4TT32-120-36**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT [WWW.OCL.COM](http://WWW.OCL.COM)

- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.
- Bottom finial option increases overall height by length of the finial.

- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- Par down light option available in combination with a variety of compact fluorescent reflectors.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



**BFL**  
BOTTOM FINIAL