




STELLAR™ SCONCE



FIXTURE WEIGHT 5 LBS



FIXTURE WEIGHT 6 LBS



FIXTURE WEIGHT 9 LBS




ST1-S1SA-18-GW-BEP



FIXTURE WEIGHT 5 LBS



FIXTURE WEIGHT 6 LBS



FIXTURE WEIGHT 10 LBS



ST1-S1SB-18-FA-PBR

MATCHING FIXTURES



page 140



page 148



page 152










page 430



page 474

FEATURES

- The classic look of crown molding creates the stately appearance of the Stellar.
- A transitional design makes it a welcome addition for both contemporary and traditional applications.
- Spun from solid, non-ferrous 0.040" thick brass, 0.040" thick copper, or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS				
 <p>ST1</p>	<p>S1SA INDOOR ADA COMPLIANT SCNCE</p> 	15	<p>GW GLOSS WHITE ACRYLIC</p> <p>MW MATTE WHITE ACRYLIC</p>	<p>PAL POLISHED ALUMINUM</p> <p>BAL BRUSHED ALUMINUM</p> <p>PTR PEWTER</p>	<p>15" </p> <p>2QD13 2@13W QD (13793.0)</p> <p>2IN40 2@40W IN (13808.0)</p>	<p>120</p> <p>277</p> <p>347</p>	<p>DMA ADVANCE® DIMMING BALLAST</p> <p>DML LUTRON® DIMMING BALLAST</p> <p>EMR REMOTE MOUNT EMERGENCY</p> <p>FUS FUSED</p> <p>ULD UL DAMP LABEL</p> <p>TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)</p>				
			<p>FA FAUX ALABASTER ACRYLIC</p> <p>NH NATURAL HORN ACRYLIC</p>	<p>PBR POLISHED BRASS</p> <p>BBR BRUSHED BRASS</p> <p>ABR ANTIQUE BRASS</p> <p>STB STATUARY BRONZE</p> <p>SNK SATIN NICKEL</p> <p>ORB OIL RUBBED BRONZE</p> <p>PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>18" </p> <p>2QD13 2@13W QD (13793.0)</p> <p>2IN40 2@40W IN (13808.0)</p> <p>24" </p> <p>2BX27 2@27W BX</p> <p>2IN40 2@40W IN</p>	<p>24</p>					
		18	<p>S1SB INDOOR SCNCE</p> 	15	<p>GW GLOSS WHITE ACRYLIC</p> <p>MW MATTE WHITE ACRYLIC</p>	<p>PAL POLISHED ALUMINUM</p> <p>BAL BRUSHED ALUMINUM</p> <p>PTR PEWTER</p>	<p>15"</p> <p>2QD13 2@13W QD (13809.0)</p> <p>2IN40 2@40W IN</p>	<p>120</p> <p>277</p> <p>347</p>	<p>DMA ADVANCE® DIMMING BALLAST</p> <p>DML LUTRON® DIMMING BALLAST</p> <p>VOL "V" STYLE OVERLAY AND BOTTOM FINIAL</p> <p>OOL "O" STYLE OVERLAY AND BOTTOM FINIAL</p> <p>EMR REMOTE MOUNT EMERGENCY (15" SIZE ONLY)</p> <p>EMI INTEGRAL EMERGENCY (18"/24" SIZES ONLY)</p> <p>FUS FUSED</p> <p>ULD UL DAMP LABEL</p> <p>TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)</p>		
					<p>FA FAUX ALABASTER ACRYLIC</p> <p>NH NATURAL HORN ACRYLIC</p>	<p>PBR POLISHED BRASS</p> <p>BBR BRUSHED BRASS</p> <p>ABR ANTIQUE BRASS</p> <p>STB STATUARY BRONZE</p> <p>SNK SATIN NICKEL</p> <p>ORB OIL RUBBED BRONZE</p> <p>PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>18"</p> <p>2QD26 2@26W QD (12201.0)</p> <p>2IN100 2@100W IN (13792.0)</p> <p>24"</p> <p>2TT32 2@32W TT (13807.0)</p> <p>2IN100 2@100W IN (13792.0)</p>	<p>277</p> <p>347</p>			
				24	<p>ET ETRUSCAN ACRYLIC</p> <p>WS WHITE SWIRL ACRYLIC</p>	<p>PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>2IN100 2@100W IN (13792.0)</p>	<p>277</p> <p>347</p>			
									<p>PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>2IN100 2@100W IN (13792.0)</p>	<p>277</p> <p>347</p>
									<p>PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>		
<p> SPECIFY CATALOG CODE</p>											

SAMPLE CODE: **ST1-S1SB-18-FA-PBR-2QD26-120-FUS**

 PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- ADA compliant version available.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.