





VT1-S1SA-24-GW-BAL

ADA



FEATURES

- The Ventura sconce features 0.25" thick aluminum laser-cut ends.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size.
- Virgin white acrylic is UV stable and UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of linear fluorescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 VT1	S1SA INDOOR ADA COMPLIANT SCONCE 	24	GW GLOSS WHITE ACRYLIC MW MATTE WHITE ACRYLIC	PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM	24"  2LF14 2@14W T5 2LF24 2@24W T5H0 (13804.0) 50"  2LF32 2@32W T8	120 277 347	DMA ADVANCE® DIMMING BALLAST DML LUTRON® DIMMING BALLAST EMR REMOTE MOUNT EMERGENCY (24" SIZE ONLY) EMI INTEGRAL EMERGENCY (50" SIZE ONLY) FUS FUSED ULD UL DAMP LABEL
		50	PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)				
<input type="checkbox"/> SPECIFY CATALOG CODE							

SAMPLE CODE: VT1-S1SA-24-GW-BAL-2LF24-120-ULD

 PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others), and requires additional anchors.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).

- Fixture is ADA compliant.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.