





VERO™ PENDANT



V01-P1CA-14-BL-SGP





V01-P1CA-14-ND-BAL



FEATURES

- The understated elegance of the Vero is achieved with its supple, curved form and cord hung suspension.
- Custom designed metal braided SJT cord.
- Optional frosted bottom diffuser with a green flame polished edge.
- The inside of the reflector is matte anodized for lamp image reduction.
- Unique airflow system circulates cool air through the fixture to maximize efficiency.
- Spun from solid, non-ferrous 0.080" thick aluminum.
- Tool-less access to lamp through bottom opening.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.


SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
 V01	<b>P1CA</b> PENDANT WITH A SINGLE POWER CORD 	14	<b>BL</b> ACRYLIC BOTTOM LENS WITH GREEN TINTED EDGE  <b>ND</b> NO DIFFUSER	<b>BAL</b> BRUSHED ALUMINUM  <b>PTD</b> PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	<b>14"</b> <b>10D26</b> 1@26W QD <b>1TT32</b> 1@32W TT <b>1TT42</b> 1@42W TT <b>1TT57</b> 1@57W TT <b>1TT70</b> 1@70W TT <b>20D26</b> 2@26W QD <b>2TT32</b> 2@32W TT <b>2TT42</b> 2@42W TT (13775.0) <b>1IN100</b> 1@100W IN	<b>120</b>  <b>277</b>  <b>347</b>	<b>34</b>	<b>DMA</b> ADVANCE® DIMMING BALLAST  <b>DML</b> LUTRON® DIMMING BALLAST  <b>EMI</b> INTEGRAL EMERGENCY REQUIRES 12" BALLAST CANOPY (SEE BELOW)  <b>FUS</b> FUSED  <b>ULD</b> UL DAMP LABEL
		18		<b>18"</b> <b>20D26</b> 2@26W QD <b>2TT32</b> 2@32W TT <b>2TT42</b> 2@42W TT <b>2TT57</b> 2@57W TT <b>2TT70</b> 2@70W TT <b>40D26</b> 4@26W QD <b>4TT32</b> 4@32W TT <b>4TT42</b> 4@42W TT <b>1IN200</b> 1@200W IN		<b>40</b>		
<input type="button" value="SPECIFY CATALOG CODE"/>								

SAMPLE CODE: **V01-P1CA-14-ND-BAL-10D26-120-34-DMA**

 **PHOTOMETRIC INFORMATION AVAILABLE AT [WWW.OCL.COM](http://WWW.OCL.COM)**

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).

- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



**EMI**  
INTEGRAL EMERGENCY REQUIRES 12" BALLAST CANOPY AND STEM