


FIXTURE WEIGHT 14 LBS



FIXTURE WEIGHT 18 LBS



VG1-S1SC-18-NA-BAL

▼ MATCHING FIXTURES



page 38



page 42





page 346



page 408

▼ FEATURES

- The Vogue arm sconce features a shallow metal bowl that sits atop a sturdy arm assembly, creating an impressive chalice that releases light upward to graze the wall surface.
- Gentle, round shape is well suited for numerous interior applications.
- Spun from solid, non-ferrous 0.064" thick aluminum.
- The arm assembly is constructed from heavy gauge steel extrusion.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 VG1	S1SC ARM SCONCE 	18	NA NONE AVAILABLE	BAL BRUSHED ALUMINUM	18"	120	DMA ADVANCE® DIMMING BALLAST
		23		PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	4QD13 4@13W QD 4QD26 4@26W QD (13773.0) 2IN100 2@100W IN (13757.0) 23" 4TT32 4@32W TT 2BX39 2@39W BX (12959.0) 3IN150 3@150W IN (13758.0)	277 347	DML LUTRON® DIMMING BALLAST EMI INTEGRAL EMERGENCY FUS FUSED ULD UL DAMP LABEL

▾ SPECIFY CATALOG CODE

SAMPLE CODE: V61-S1SC-18-NA-BAL-4QD26-120-FUS

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.