


VOYAGER™ PENDANT



VY1-P2ED-26-GW-SMP





MATCHING FIXTURES



page 190

FEATURES

- An ultra-shallow diffuser seamlessly completes the form of the simple spun aluminum trim.
- The design is further accented with the concentric ribs in the trim.
- Spun from solid, non-ferrous 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size.
- Virgin white acrylic is UV stable and UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
 <p>VY1</p>	<p>P2ED DOUBLE CLUSTER PENDANT WITH 2 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM CLUSTER BODY TO CANOPY</p>  <p>P3ED TRIPLE CLUSTER PENDANT WITH 3 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM CLUSTER BODY TO CANOPY</p>  <p>P4ED QUAD CLUSTER PENDANT WITH 4 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM CLUSTER BODY TO CANOPY</p> 	26	<p>GW GLOSS WHITE ACRYLIC</p> <p>MW MATTE WHITE ACRYLIC</p>	<p>PAL POLISHED ALUMINUM</p> <p>BAL BRUSHED ALUMINUM</p> <p>PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p> <p>NOTE: ON ALL BRASS AND PLATED FINISHES, CLUSTER ARMS WILL BE POWDER COAT PAINTED.</p>	<p>26"</p> <p>8QD26 8@26W QD (11091.0)</p> <p>4BX39 4@39W BX (11095.0)</p> <p>3IN150 3@150W IN (13742.0)</p> <p>NOTE: LAMPING LISTED IS PER BOWL.</p>	120 277 347	48	<p>DMA ADVANCE® DIMMING BALLAST</p> <p>DML LUTRON® DIMMING BALLAST</p> <p>EMI INTEGRAL EMERGENCY</p> <p>FUS FUSED</p> <p>TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)</p> <p>ULD UL DAMP LABEL</p>
<p>▾ SPECIFY CATALOG CODE</p>								

SAMPLE CODE: VY1-P2ED-26-GW-SMP-4BX39-120-48-DML

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture requires structural mounting.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Dual circuiting is standard on multi-ballast fixtures. Consult factory for details or other circuiting options.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- If sloped-ceiling adapter is required, consult factory for details.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.