



## WESTPORT™ PENDANT



FIXTURE WEIGHT 9 LBS



FIXTURE WEIGHT 18 LBS



WP1-P1AA-14-FR-SGP



WP1-P1AA-14-CL-BAL



### MATCHING FIXTURES



page 102

### FEATURES

- The Westport is OCL's updated version of a classic, industrial style pendant.
- Injection molded prismatic acrylic diffuser.
- Laser-cut slots in aluminum fitter allow circulation to keep lamps cooler for durability and efficiency.
- Unique bottom diffuser eliminates harsh glare from lamps while still transmitting light.
- Canopy, fitter and bottom trim ring are spun from solid, non-ferrous 0.064" thick aluminum.
- Tool-less access to lamp through bottom opening.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.


SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
 <p>WP1</p>	<p>P1AA PENDANT WITH A SINGLE CENTER STEM</p> 	14	<b>CL</b> CLEAR PRISMATIC ACRYLIC	<b>BAL</b> BRUSHED ALUMINUM <b>PTD</b> PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	<b>14"</b> <b>10D26</b> 1@26W QD <b>1TT32</b> 1@32W TT <b>1TT42</b> 1@42W TT (12392.0) <b>1TT57</b> 1@57W TT <b>1TT70</b> 1@70W TT	<b>120</b> <b>277</b> <b>347</b>	<b>34</b>	<b>DMA</b> ADVANCE® DIMMING BALLAST REQUIRES 12" BALLAST CANOPY (SEE BELOW)
			<b>FR</b> FROSTED PRISMATIC ACRYLIC					<b>DML</b> LUTRON® DIMMING BALLAST REQUIRES 12" BALLAST CANOPY (SEE BELOW)
			<b>FG</b> FROSTED GREEN PRISMATIC ACRYLIC					<b>EMI</b> INTEGRAL EMERGENCY REQUIRES 12" BALLAST CANOPY (SEE BELOW)
			<b>FB</b> FROSTED BLUE PRISMATIC ACRYLIC					<b>FUS</b> FUSED
			<b>AM</b> AMBER PRISMATIC ACRYLIC					<b>ULD</b> UL DAMP LABEL
			<b>RP</b> RED PRISMATIC ACRYLIC					
		18	<b>GR</b> GREEN PRISMATIC ACRYLIC	<b>4QD26</b> 4@26W QD <b>4TT32</b> 4@32W TT (13751.0) <b>4TT42</b> 4@42W TT <b>2TT57</b> 2@57W TT <b>2TT70</b> 2@70W TT <b>1IN200</b> 1@200W IN	<b>18"</b> <b>40</b>			
			<b>BP</b> BLUE PRISMATIC ACRYLIC					
			<b>NOTE: 18" NOT AVAILABLE IN COLORED ACRYLIC</b>					
			<input type="button" value="SPECIFY CATALOG CODE"/>					

SAMPLE CODE: WP1-P1AA-14-CL-BAL-1TT32-120-34-ULD

↑ PHOTOMETRIC INFORMATION AVAILABLE AT [WWW.OCL.COM](http://WWW.OCL.COM)

- Fixture mounts to a standard 4" J-box (supplied by others), and features a 45-degree sloped-ceiling canopy.
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Maximum overall height subject to ballast specification. Consult factory for details.

- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- For metal halide lamping contact factory.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.



**DMA/DML/EMI**  
REQUIRES 12" BALLAST CANOPY