


FIXTURE WEIGHT 5 LBS



WW1-S1SA-12-GW-BAL

ADA



FIXTURE WEIGHT 5 LBS







WW2-S1SA-12-GW-SGP

ADA



**FEATURES**

- The Wing sconce features a 0.125" thick laser-cut and formed aluminum frame.
- Decorative frame available with straight or curved edges.
- 3/16" thick extruded virgin white acrylic diffuser is UV stable and UL-94 HB Flame Class rated.
- Faux acrylic is thermally formed and colors are mixed completely through to avoid noticeable fading.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 <b>WW1</b>	<b>S1SA</b> INDOOR ADA COMPLIANT SCONCE 	12	<b>GW</b> GLOSS WHITE ACRYLIC	<b>PAL</b> POLISHED ALUMINUM	<b>12"</b> 	120	<b>DMA</b> ADVANCE® DIMMING BALLAST
			<b>MW</b> MATTE WHITE ACRYLIC	<b>BAL</b> BRUSHED ALUMINUM			<b>20D13</b> 2@13W QD
 <b>WW2</b>			<b>FA</b> FAUX ALABASTER ACRYLIC	<b>PTD</b> PAINTED - SPECIFY CODE (EX. <b>BKP</b> FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)	<b>10D26</b> 1@26W QD (13785.0)	347	<b>EMR</b> REMOTE MOUNT EMERGENCY
			<b>NH</b> NATURAL HORN ACRYLIC				
			<b>ET</b> ETRUSCAN ACRYLIC				<b>ULD</b> UL DAMP LABEL
			<b>WS</b> WHITE SWIRL ACRYLIC				

☑ SPECIFY CATALOG CODE

SAMPLE CODE: **WW2-S1SA-12-GW-SGP-10D26-120-ULD**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT [WWW.OCL.COM](http://WWW.OCL.COM)

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- Fixture is ADA compliant.
- For photometric data, please visit [www.ocl.com](http://www.ocl.com).
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.