



Camelot™

CEILING

FEATURES

- THE CAMELOT IS A REPRODUCTION OF A HISTORICAL CLASSIC
- THE OPTIONAL V-STYLE OVERLAY AND ACORN STYLE CAST BRASS BOTTOM FINIAL ADD ANOTHER LEVEL OF ELEGANCE
- CONSTRUCTED WITH SOLID, NON-FERROUS BRASS
- THERMALLY FORMED ACRYLIC RANGES FROM 3/16" TO 1/4" THICK, DEPENDING ON SIZE. VIRGIN WHITE ACRYLIC IS UV STABLE, AND ALL FAUX ACRYLIC COLORS ARE MIXED COMPLETELY THROUGH TO AVOID NOTICEABLE FADING
- WHITE ACRYLIC IS UL-94 HB FLAME CLASS RATING
- OCL METAL FINISHES ARE APPLIED BY HAND AND RECEIVE A PROTECTIVE CLEAR COAT



CATALOG CODES

CM1	-	C1NA	-	C	-	D	-	E	-	F	-	G	-	H	-	I
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS

SPECIFY CATALOG CODE

A	B	C	D	E
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH
 CM1 CAMELOT	C1NA SURFACE CEILING MOUNT	17	GW GLOSS WHITE ACRYLIC	POWDER COAT FINISHES BKP BLACK BMP BRASS METALLIC BNP BRONZE BTP BLACK TEXTURED GRP GRAPHITE GLP GOLDTASTIC MWP MATTE WHITE SGP STEEL GRAY SMP SILVER METALLIC SWP SKY WHITE WTP WHITE TEXTURED
		25	PREMIUM ACRYLIC MW MATTE WHITE ACRYLIC FA FAUX ALABASTER ACRYLIC WS WHITE SWIRL ACRYLIC	

F	G	H	I
LIGHT SOURCE	VOLTAGE	CONTROL	OPTIONS
LED OUTPUT LED1 COLOR TEMP 27K 30K 35K 40K	UNV 120-277	DM1 0-10V DIMMING 1%	VOL "V" STYLE OVERLAY AND BOTTOM FINIAL (SEE RIGHT) MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP) VOL
2IN60 SCREW IN OUTPUT 2 - E26 MEDIUM BASE SOCKET - A19 LAMP (17", 25") 60W MAX INC PER LAMP (BY OTHERS)	120V (SCREW IN ONLY)	LEAVE BLANK FOR SCREW IN	

SAMPLE CODE: CM1-C1NA-17-MW-BAL-LED1/35K-UNV-DM1

MODS, NOTES, & COMMENTS

LUMENS AND WATTAGE CHART		17	25
LED1	LUMENS DELIVERED	1250	1250
	SYSTEM WATTAGE	25	25

This chart was created for a 35K color temp with standard white acrylic. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. LED wattage and lumen data approx. pending LM-79 testing.