



# Camelot™

## PENDANT

### FEATURES

- THE CAMELOT IS A RECREATION OF A HISTORICAL CLASSIC
- CAST FROM SOLID, NON-FERROUS BRASS, THE TRIM RING FEATURES THE CLASSIC EGG-AND-DART ARCHITECTURAL DETAIL
- THE OPTIONAL V-STYLE OVERLAY AND ACORN STYLE CAST BRASS BOTTOM FINIAL ADDS ANOTHER LEVEL OF ELEGANCE
- THERMALLY FORMED ACRYLIC RANGES FROM 3/16" TO 1/4" THICK, DEPENDING ON SIZE. VIRGIN WHITE ACRYLIC IS UV STABLE, AND ALL FAUX ACRYLIC COLORS ARE MIXED COMPLETELY THROUGH TO AVOID NOTICEABLE FADING
- WHITE ACRYLIC IS UL-94 HB FLAME CLASS RATING
- OCL METAL FINISHES ARE APPLIED BY HAND AND RECEIVE A PROTECTIVE CLEAR COAT



### CATALOG CODES

A	B	C	E	F	H	I	J		
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LIGHT SOURCE	VOLTAGE	OAH	CONTROL	OPTIONS

#### SPECIFY CATALOG CODE

A	B	C	D	E
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH
<p><b>CM1</b> CAMELOT (SHALLOW DIFFUSER)</p>	<p><b>PIAJ</b> PENDANT WITH 3 ANGLED REEDED STEMS TO CANOPY AND A SINGLE REEDED CENTER STEM FROM TRIM RING TO CANOPY <b>NOTE: 25" SIZES ONLY</b></p>	25	<p><b>GW</b> GLOSS WHITE ACRYLIC</p> <p><b>PREMIUM ACRYLIC</b></p> <p><b>MW</b> MATTE WHITE ACRYLIC</p> <p><b>FA</b> FAUX ALABASTER ACRYLIC</p> <p><b>WS</b> WHITE SWIRL ACRYLIC</p>	<p><b>POWDER COAT FINISHES</b></p> <p><b>BKP</b> BLACK</p> <p><b>BMP</b> BRASS METALLIC</p> <p><b>BNP</b> BRONZE</p> <p><b>BTP</b> BLACK TEXTURED</p> <p><b>GRP</b> GRAPHITE</p> <p><b>GLP</b> GOLDTASTIC</p> <p><b>MWP</b> MATTE WHITE</p> <p><b>SGP</b> STEEL GRAY</p> <p><b>SMP</b> SILVER METALLIC</p> <p><b>SWP</b> SKY WHITE</p> <p><b>WTP</b> WHITE TEXTURED</p>
	<p><b>PIAK</b> PENDANT WITH 3 ANGLED REEDED STEMS AND A CENTER REEDED STEM TO COLLECTOR AND A SINGLE CENTER CHAIN FROM COLLECTOR TO CANOPY <b>NOTE: 32" SIZE ONLY</b></p>	32		<p><b>PREMIUM METAL FINISHES</b></p> <p><b>PTR</b> PEWTER</p> <p><b>PBR</b> POLISHED BRASS</p> <p><b>BBR</b> BRUSHED BRASS</p> <p><b>ABR</b> ANTIQUE BRASS</p> <p><b>STB</b> STATUARY BRONZE</p> <p><b>SNK</b> SATIN NICKEL</p> <p><b>ORB</b> OIL RUBBED BRONZE</p>

F	G	H	I	J
LIGHT SOURCE	VOLTAGE	OAH	CONTROL	OPTIONS
<p><b>LED OUTPUT</b></p> <p><b>LED1</b></p> <p><b>LED2</b></p> <p><b>NOTE: TOP LENS STANDARD IN LED</b></p>	<p><b>COLOR TEMP</b></p> <p><b>27K</b></p> <p><b>30K</b></p> <p><b>35K</b></p> <p><b>40K</b></p>	<p><b>UNV</b> 120-277</p>	<p><b>SPECIFY IN INCHES</b></p>	<p><b>DM1</b> 0-10V DIMMING 1%</p>
<p><b>3IN100</b> 3 - E26 MEDIUM BASE SOCKET - A19 LAMP (24", 31") 100W MAX INC PER LAMP (BY OTHERS)</p> <p><b>3IN150</b> 3 - E26 MEDIUM BASE SOCKET - A19 LAMP (42") 150W MAX INC PER LAMP (BY OTHERS)</p>	<p><b>LEAVE BLANK FOR SCREW IN</b></p>	<p><b>120V</b> (SCREW IN ONLY)</p>	<p><b>LEAVE BLANK FOR SCREW IN</b></p>	<p><b>CIB</b> CLEAR INNER BOWL</p> <p><b>VOL</b> "V" STYLE OVERLAY AND BOTTOM FINIAL (SEE RIGHT)</p> <p><b>MOD</b> MODIFIED LUMINAIRE (CONTACT LOCAL REP)</p> <p><b>VOL</b></p>

SAMPLE CODE: CM1-PIAJ-25-MW-ORB-LED1/27K-UNV-48-DM1-VOL

LUMENS AND WATTAGE CHART		25	32
<b>LED1</b>	LUMENS DELIVERED	4500	4500
	SYSTEM WATTAGE	50	50
<b>LED2</b>	LUMENS DELIVERED	9100	9100
	SYSTEM WATTAGE	105	105

### MODS, NOTES, & COMMENTS

This chart was created for a 35K color temp with standard white acrylic. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. LED wattage and lumen data approx. pending LM-79 testing.