



# Ella™

CEILING

**FEATURES**

- THE TRIM RING OF THE ELLA IS SIMPLE AND ELEGANT
- THE ELLA'S TRANSITIONAL DESIGN MAKES IT PERFECTLY SUITED FOR BOTH CONTEMPORARY AND TRADITIONAL APPLICATIONS
- CONSTRUCTED WITH SOLID, NON-FERROUS BRASS OR ALUMINUM
- THERMALLY FORMED ACRYLIC RANGES FROM 3/16" TO 1/4" THICK, DEPENDING ON SIZE. VIRGIN WHITE ACRYLIC IS UV STABLE, AND ALL FAUX ACRYLIC COLORS ARE MIXED COMPLETELY THROUGH TO AVOID NOTICEABLE FADING
- WHITE ACRYLIC IS UL-94 HB FLAME CLASS RATING
- OCL METAL FINISHES ARE APPLIED BY HAND AND RECEIVE A PROTECTIVE CLEAR COAT



**CATALOG CODES**

<b>EA1</b>	-	<b>C1NA</b>	-	<b>C</b>	-	<b>D</b>	-	<b>E</b>	-	<b>F</b>	-	<b>G</b>	-	<b>H</b>	-	<b>I</b>
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS

SPECIFY CATALOG CODE		A	B	C	D	E		F	G	H	I		
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH		LIGHT SOURCE	VOLTAGE	CONTROL	OPTIONS				
 <b>EA1</b> ELLA	<b>C1NA</b> SURFACE CEILING MOUNT	<b>17</b>	<b>GW</b> GLOSS WHITE ACRYLIC  <b>PREMIUM ACRYLIC</b> <b>MW</b> MATTE WHITE ACRYLIC <b>FA</b> FAUX ALABASTER ACRYLIC <b>WS</b> WHITE SWIRL ACRYLIC	<b>POWDER COAT FINISHES</b> <b>BKP</b> BLACK <b>BMP</b> BRASS METALLIC <b>BNP</b> BRONZE <b>BTP</b> BLACK TEXTURED <b>GRP</b> GRAPHITE <b>GLP</b> GOLDTASTIC <b>MWP</b> MATTE WHITE <b>SGP</b> STEEL GRAY <b>SMP</b> SILVER METALLIC <b>SWP</b> SKY WHITE <b>WTP</b> WHITE TEXTURED		<b>PREMIUM METAL FINISHES</b> <b>PAL</b> POLISHED ALUMINUM <b>BAL</b> BRUSHED ALUMINUM <b>PTR</b> PEWTER <b>PBR</b> POLISHED BRASS <b>BBR</b> BRUSHED BRASS <b>ABR</b> ANTIQUE BRASS <b>STB</b> STATUARY BRONZE <b>SNK</b> SATIN NICKEL <b>ORB</b> OIL RUBBED BRONZE		<b>UNV</b> 120-277	<b>DM1</b> 0-10V DIMMING 1%	<b>EDB</b> EGG AND DART BANDING (SEE RIGHT) <b>MOD</b> MODIFIED LUMINAIRE (CONTACT LOCAL REP)			 <b>EDB</b>
		<b>2IN60</b> 2 - E26 MEDIUM BASE SOCKET - A19 LAMP (17") 60W MAX INC PER LAMP (BY OTHERS)  <b>2IN100</b> 2 - E26 MEDIUM BASE SOCKET - A19 LAMP (27") 100W MAX INC PER LAMP (BY OTHERS)		<b>LEAVE BLANK FOR SCREW IN</b>	<b>120V</b> (SCREW IN ONLY)	<b>LEAVE BLANK FOR SCREW IN</b>							
<b>SAMPLE CODE: EA1-C1NA-17-MW-BAL-LED1/35K-UNV-DM1</b>													

**MODS, NOTES, & COMMENTS**

LUMENS AND WATTAGE CHART		17	27
<b>LED1</b>	LUMENS DELIVERED	1250	1250
	SYSTEM WATTAGE	25	25

This chart was created for a 35K color temp with standard white acrylic. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. LED wattage and lumen data approx. pending LM-79 testing.