



Ella™

PENDANT


FEATURES


- THE SIMPLE AND ELEGANT TRIM RING OF THE ELLA MAKES IT PERFECTLY SUITED FOR BOTH CONTEMPORARY AND TRADITIONAL APPLICATIONS
- CONSTRUCTED WITH SOLID, NON-FERROUS BRASS OR ALUMINUM
- THERMALLY FORMED ACRYLIC RANGES FROM 3/16" TO 1/4" THICK, DEPENDING ON SIZE. VIRGIN WHITE ACRYLIC IS UV STABLE, AND ALL FAUX ACRYLIC COLORS ARE MIXED COMPLETELY THROUGH TO AVOID NOTICEABLE FADING
- WHITE ACRYLIC IS UL-94 HB FLAME CLASS RATING
- OCL METAL FINISHES ARE APPLIED BY HAND AND RECEIVE A PROTECTIVE CLEAR COAT



CATALOG CODES

EA1	B	C	E	F /	H	I	J
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LIGHT SOURCE	VOLTAGE	OPTIONS

SPECIFY CATALOG CODE		A	B	C	D	E	
SERIES		HANGING SYSTEM		SIZE	DIFFUSER	FINISH	
 EA1 ELLA	PIAA	PENDANT WITH A SINGLE CENTER STEM		27	GW GLOSS WHITE ACRYLIC	POWDER COAT FINISHES BKP BLACK BMP BRASS METALLIC BNP BRONZE BTP BLACK TEXTURED GRP GRAPHITE GLP GOLDTASTIC MWP MATTE WHITE SGP STEEL GRAY SMP SILVER METALLIC SWP SKY WHITE WTP WHITE TEXTURED	
	PIAH	PENDANT WITH 3 ANGLED STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY		34	PREMIUM ACRYLIC		PREMIUM METAL FINISHES PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM PTR PEWTER PBR POLISHED BRASS BBR BRUSHED BRASS ABR ANTIQUE BRASS STB STATUARY BRONZE SNK SATIN NICKEL ORB OIL RUBBED BRONZE
	PIAI	PENDANT WITH 3 ANGLED REEDED STEMS TO COLLECTOR AND A SINGLE REEDED CENTER STEM FROM TRIM RING TO CANOPY		42	FA FAUX ALABASTER ACRYLIC WS WHITE SWIRL ACRYLIC		

F		G		H	I	J	
LIGHT SOURCE		VOLTAGE		OAHS	CONTROL	OPTIONS	
LED OUTPUT LED1 LED2 NOTE: TOP LENS STANDARD IN LED	COLOR TEMP 27K 30K 35K 40K	UNV 120-277		SPECIFY IN INCHES	DM1 0-10V DIMMING 1%	CIB CLEAR INNER BOWL EDB EGG AND DART BANDING (SEE RIGHT) MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP)	 EDB
3IN150 3 - E26 MEDIUM BASE SOCKET - A19 LAMP (27") 150W MAX INC PER LAMP (BY OTHERS) 6IN150 6 - E26 MEDIUM BASE SOCKET - A19 LAMP (34") 150W MAX INC PER LAMP (BY OTHERS) 8IN150 8 - E26 MEDIUM BASE SOCKET - A19 LAMP (42") 150W MAX INC PER LAMP (BY OTHERS)	LEAVE BLANK FOR SCREW IN	120V (SCREW IN ONLY)			LEAVE BLANK FOR SCREW IN		

SAMPLE CODE: EA1-PIAA-27-GW-BKP-LED1/30K-UNV-48-DM1-EDB

LUMENS AND WATTAGE CHART		27	34	42
LED1	LUMENS DELIVERED	4500	4500	4500
	SYSTEM WATTAGE	50	50	50
LED2	LUMENS DELIVERED	9100	9100	9100
	SYSTEM WATTAGE	105	105	105

This chart was created for a 35K color temp with standard white acrylic. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. LED wattage and lumen data approx. pending LM-79 testing.

MODS, NOTES, & COMMENTS