



Ella™

SCENCE

FEATURES


- THE SIMPLE AND ELEGANT TRIM RING OF THE ELLA MAKES IT PERFECTLY SUITED FOR BOTH CONTEMPORARY AND TRADITIONAL APPLICATIONS
- CONSTRUCTED WITH SOLID, NON-FERROUS BRASS OR ALUMINUM
- THERMALLY FORMED ACRYLIC RANGES FROM 3/16" TO 1/4" THICK, DEPENDING ON SIZE. VIRGIN WHITE ACRYLIC IS UV STABLE, AND ALL FAUX ACRYLIC COLORS ARE MIXED COMPLETELY THROUGH TO AVOID NOTICEABLE FADING
- WHITE ACRYLIC IS UL-94 HB FLAME CLASS RATING
- OCL METAL FINISHES ARE APPLIED BY HAND AND RECEIVE A PROTECTIVE CLEAR COAT




CATALOG CODES

| | | | | | | | | | | | | | | | | |
|------------|---|----------------|---|----------|---|----------|---|----------|---|--------------|---|----------|---|----------|---|----------|
| EA1 | - | S1SA | - | C | - | D | - | E | - | F | - | G | - | H | - | I |
| SERIES | | HANGING SYSTEM | | SIZE | | DIFFUSER | | FINISH | | LIGHT SOURCE | | VOLTAGE | | CONTROL | | OPTIONS |

SPECIFY CATALOG CODE

| A | B | C | D | E |
|---|---|----------------------------|---|---|
| SERIES | HANGING SYSTEM | SIZE | DIFFUSER | FINISH |
|  EA1 ELLA | S1SA INDOOR ADA COMPLIANT SCENCE | 17 27 | GW GLOSS WHITE ACRYLIC PREMIUM ACRYLIC MW MATTE WHITE ACRYLIC FA FAUX ALABASTER ACRYLIC WS WHITE SWIRL ACRYLIC | POWDER COAT FINISHES BKP BLACK BMP BRASS METALLIC BNP BRONZE BTP BLACK TEXTURED GRP GRAPHITE GLP GOLDTASTIC MWP MATTE WHITE SGP STEEL GRAY SMP SILVER METALLIC SWP SKY WHITE WTP WHITE TEXTURED PREMIUM METAL FINISHES PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM PTR PEWTER PBR POLISHED BRASS BBR BRUSHED BRASS ABR ANTIQUE BRASS STB STATUARY BRONZE SNK SATIN NICKEL ORB OIL RUBBED BRONZE |

| F | G | H | I |
|--|---|-----------------------------|--|
| LIGHT SOURCE | VOLTAGE | CONTROL | OPTIONS |
| LED OUTPUT LED1 NOTE: TOP LENS STANDARD IN LED | COLOR TEMP 27K 30K 35K 40K | UNV 120-277 | DM1 0-10V DIMMING 1% EDB EGG AND DART BANDING (SEE RIGHT) MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP) |
| SCREW IN OUTPUT 2IN40 2 - E12 BASE SOCKET - B10 LAMP 40W MAX INC PER LAMP (BY OTHERS) | LEAVE BLANK FOR SCREW IN | 120V (SCREW IN ONLY) | LEAVE BLANK FOR SCREW IN  EDB |

SAMPLE CODE: EA1-S1SA-17-MW-BAL-LED1/27K-UNV-DM1

MODS, NOTES, & COMMENTS

| LUMENS AND WATTAGE CHART | | 17 | 27 |
|--------------------------|------------------|------|------|
| LED1 | LUMENS DELIVERED | 1125 | 1125 |
| | SYSTEM WATTAGE | 15 | 15 |

This chart was created for a 35K color temp with standard white acrylic. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. LED wattage and lumen data approx. pending LM-79 testing.