



Horizon™

PENDANT

FEATURES

- THE HORIZON FEATURES A LOW-PROFILE, MINIMALIST SQUARE TRIM
- A TRANSITIONAL DESIGN MAKES IT A WELCOME ADDITION TO BOTH CONTEMPORARY AND TRADITIONAL APPLICATIONS
- CONSTRUCTED WITH SOLID, NON-FERROUS BRASS OR ALUMINUM
- THERMALLY FORMED ACRYLIC RANGES FROM 3/16" TO 1/4" THICK, DEPENDING ON SIZE. VIRGIN WHITE ACRYLIC IS UV STABLE, AND ALL FAUX ACRYLIC COLORS ARE MIXED COMPLETELY THROUGH TO AVOID NOTICEABLE FADING
- WHITE ACRYLIC IS UL-94 HB FLAME CLASS RATING
- OCL METAL FINISHES ARE APPLIED BY HAND AND RECEIVE A PROTECTIVE CLEAR COAT



CATALOG CODES

HR1	-	B	-	C	-	E	-	F	-	H	-	I	-	J				
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		OAH		CONTROL		OPTIONS

SPECIFY CATALOG CODE

A	B		C	D		E	
SERIES	HANGING SYSTEM		SIZE	DIFFUSER		FINISH	
 HR1 HORIZON	PIAA	PIAA PENDANT WITH A SINGLE CENTER STEM	26	GW	GLOSS WHITE ACRYLIC		POWDER COAT FINISHES BKP BLACK BMP BRASS METALLIC BNP BRONZE BTP BLACK TEXTURED GRP GRAPHITE GLP GOLDTASTIC MWP MATTE WHITE SGP STEEL GRAY SMP SILVER METALLIC SWP SKY WHITE WTP WHITE TEXTURED
	PIAH	PENDANT WITH 3 ANGLED STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY	33	PREMIUM ACRYLIC		PREMIUM METAL FINISHES PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM PTR PEWTER PBR POLISHED BRASS BBR BRUSHED BRASS ABR ANTIQUE BRASS STB STATUARY BRONZE SNK SATIN NICKEL ORB OIL RUBBED BRONZE	
	PIED	PENDANT WITH 3 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY	41	MW	MATTE WHITE ACRYLIC		
				FA	FAUX ALABASTER ACRYLIC		
				WS	WHITE SWIRL ACRYLIC		

F		G	H	I	J
LIGHT SOURCE		VOLTAGE	OAH	CONTROL	OPTIONS
LED OUTPUT LED1 LED2 NOTE: TOP LENS STANDARD IN LED	COLOR TEMP 27K 30K 35K 40K	UNV 120-277	SPECIFY IN INCHES	DM1 0-10V DIMMING 1%	MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP)
3IN150 3 - E26 MEDIUM BASE SOCKET - A19 LAMP (26") 150W MAX INC PER LAMP (BY OTHERS) 6IN150 6 - E26 MEDIUM BASE SOCKET - A19 LAMP (33") 150W MAX INC PER LAMP (BY OTHERS) 8IN150 8 - E26 MEDIUM BASE SOCKET - A19 LAMP (41") 150W MAX INC PER LAMP (BY OTHERS)	LEAVE BLANK FOR SCREW IN	120V (SCREW IN ONLY)		LEAVE BLANK FOR SCREW IN	

SAMPLE CODE: HR1-PIED-33-MW-PAL-LED1/35K-UNV-48-DM1

LUMENS AND WATTAGE CHART		26	33	41
LED1	LUMENS DELIVERED	4500	4500	4500
	SYSTEM WATTAGE	50	50	50
LED2	LUMENS DELIVERED	9100	9100	9100
	SYSTEM WATTAGE	105	105	105

MODS, NOTES, & COMMENTS

This chart was created for a 35K color temp with standard white acrylic. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. LED wattage and lumen data approx. pending LM-79 testing.