



# Horizon™

## SCENCE


### FEATURES

- THE HORIZON FEATURES A LOW-PROFILE, MINIMALIST SQUARE TRIM
- A TRANSITIONAL DESIGN MAKES IT A WELCOME PIECE FOR BOTH CONTEMPORARY AND TRADITIONAL APPLICATIONS
- CONSTRUCTED WITH SOLID, NON-FERROUS BRASS OR ALUMINUM
- THERMALLY FORMED ACRYLIC RANGES FROM 3/16" TO 1/4" THICK, DEPENDING ON SIZE. VIRGIN WHITE ACRYLIC IS UV STABLE, AND ALL FAUX ACRYLIC COLORS ARE MIXED COMPLETELY THROUGH TO AVOID NOTICEABLE FADING
- WHITE ACRYLIC IS UL-94 HB FLAME CLASS RATING
- OCL METAL FINISHES ARE APPLIED BY HAND AND RECEIVE A PROTECTIVE CLEAR COAT



### CATALOG CODES

|            |   |                |   |          |   |          |   |          |   |              |   |          |   |          |   |          |
|------------|---|----------------|---|----------|---|----------|---|----------|---|--------------|---|----------|---|----------|---|----------|
| <b>HR1</b> | - | <b>S1SA</b>    | - | <b>C</b> | - | <b>D</b> | - | <b>E</b> | - | <b>F</b>     | - | <b>G</b> | - | <b>H</b> | - | <b>I</b> |
| SERIES     |   | HANGING SYSTEM |   | SIZE     |   | DIFFUSER |   | FINISH   |   | LIGHT SOURCE |   | VOLTAGE  |   | CONTROL  |   | OPTIONS  |

| SPECIFY CATALOG CODE   |  | A  | B   | C                           | D   | E  |   |
|--|--|--|---|-----------------------------|---|--|---|
|  |  | SERIES   | HANGING SYSTEM                                | SIZE                        | DIFFUSER  | FINISH   |   |
|  |  | <b>S1SA</b>  | INDOOR ADA COMPLIANT SCENCE                   | <b>16</b><br><b>26</b>      | <b>GW</b> GLOSS WHITE ACRYLIC<br><b>PREMIUM ACRYLIC</b><br><b>MW</b> MATTE WHITE ACRYLIC<br><b>FA</b> FAUX ALABASTER ACRYLIC<br><b>WS</b> WHITE SWIRL ACRYLIC | <b>POWDER COAT FINISHES</b><br><b>BKP</b> BLACK<br><b>BMP</b> BRASS METALLIC<br><b>BNP</b> BRONZE<br><b>BTP</b> BLACK TEXTURED<br><b>GRP</b> GRAPHITE<br><b>GLP</b> GOLDTASTIC<br><b>MWP</b> MATTE WHITE<br><b>SGP</b> STEEL GRAY<br><b>SMP</b> SILVER METALLIC<br><b>SWP</b> SKY WHITE<br><b>WTP</b> WHITE TEXTURED | <b>PREMIUM METAL FINISHES</b><br><b>PAL</b> POLISHED ALUMINUM<br><b>BAL</b> BRUSHED ALUMINUM<br><b>PTR</b> PEWTER<br><b>PBR</b> POLISHED BRASS<br><b>BBR</b> BRUSHED BRASS<br><b>ABR</b> ANTIQUE BRASS<br><b>STB</b> STATUARY BRONZE<br><b>SNK</b> SATIN NICKEL<br><b>ORB</b> OIL RUBBED BRONZE |
|  |  | F  |   | G                           | H   | I  |   |
|  |  | LIGHT SOURCE   |   | VOLTAGE                     | CONTROL   | OPTIONS  |   |
|  |  | <b>LED OUTPUT LED1</b><br><b>NOTE: TOP LENS STANDARD IN LED</b>  | <b>COLOR TEMP</b><br>27K<br>30K<br>35K<br>40K | <b>UNV</b> 120-277          | <b>DM1</b> 0-10V DIMMING 1%   | <b>MOD</b> MODIFIED LUMINAIRE (CONTACT LOCAL REP)  |   |
|  |  | <b>SCREW IN OUTPUT</b><br><b>2IN40</b> 2 - E12 BASE SOCKET - B10 LAMP 40W MAX INC PER LAMP (BY OTHERS) | <b>LEAVE BLANK FOR SCREW IN</b>               | <b>120V</b> (SCREW IN ONLY) | <b>LEAVE BLANK FOR SCREW IN</b>   |  |   |

SAMPLE CODE: HR1-S1SA-16-MW-BBR-LED1/27K-UNV-DM1

### MODS, NOTES, & COMMENTS

| LUMENS AND WATTAGE CHART |                  | 16   | 26   |
|--------------------------|------------------|------|------|
| <b>LED1</b>              | LUMENS DELIVERED | 1125 | 1125 |
|                          | SYSTEM WATTAGE   | 15   | 15   |

This chart was created for a 35K color temp with standard white acrylic. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. LED wattage and lumen data approx. pending LM-79 testing.