



Monaco™

CEILING


FEATURES

- THE MONACO FEATURES A SHALLOW ACRYLIC DIFFUSER ACCENTED BY A ROLLED BRASS OR ALUMINUM RING; ITS TRANSITIONAL DESIGN MAKES THE MONACO A WELCOME PIECE FOR BOTH CONTEMPORARY AND TRADITIONAL APPLICATIONS
- CONSTRUCTED WITH SOLID, NON-FERROUS BRASS OR ALUMINUM
- THERMALLY FORMED ACRYLIC RANGES FROM 3/16" TO 1/4" THICK, DEPENDING ON SIZE. VIRGIN WHITE ACRYLIC IS UV STABLE, AND ALL FAUX ACRYLIC COLORS ARE MIXED COMPLETELY THROUGHOUT TO AVOID NOTICEABLE FADING
- WHITE ACRYLIC IS UL-94 HB FLAME CLASS RATING
- OCL METAL FINISHES ARE APPLIED BY HAND AND RECEIVE A PROTECTIVE CLEAR COAT



CATALOG CODES

MN1	-	C1NA	-	C	-	D	-	E	-	F	-	UNV	-	DM1	-	I
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS

SPECIFY CATALOG CODE		A	B	C	D	E	
		SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	
 <p>MN1 MONACO</p>		C1NA	SURFACE CEILING MOUNT	16 19 23	GW GLOSS WHITE ACRYLIC PREMIUM ACRYLIC MW MATTE WHITE ACRYLIC FA FAUX ALABASTER ACRYLIC WS WHITE SWIRL ACRYLIC	POWDER COAT FINISHES BKP BLACK BMP BRASS METALLIC BNP BRONZE BTP BLACK TEXTURED GRP GRAPHITE GLP GOLDTASTIC MWP MATTE WHITE SGP STEEL GRAY SMP SILVER METALLIC SWP SKY WHITE WTP WHITE TEXTURED	PREMIUM METAL FINISHES PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM PTR PEWTER PBR POLISHED BRASS BBR BRUSHED BRASS ABR ANTIQUE BRASS STB STATUARY BRONZE SNK SATIN NICKEL ORB OIL RUBBED BRONZE

F		G	H	I
LIGHT SOURCE		VOLTAGE	CONTROL	OPTIONS
LED OUTPUT LED1	COLOR TEMP 27K 30K 35K 40K	UNV 120-277	DM1 0-10V DIMMING 1%	MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP)

SAMPLE CODE: MN1-C1NA-16-MW-BAL-LED1/35K-UNV-DM1

MODS, NOTES, & COMMENTS

LUMENS AND WATTAGE CHART		16	19	23
LED1	LUMENS DELIVERED	1250	1250	1250
	SYSTEM WATTAGE	25	25	25

This chart was created for a 35K color temp with standard white acrylic. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. LED wattage and lumen data approx. pending LM-79 testing.