



# Monaco™

PENDANT

**FEATURES**

- THE MONACO FEATURES A SHALLOW ACRYLIC DIFFUSER ACCENTED BY A ROLLED BRASS OR ALUMINUM RING
- CONSTRUCTED WITH SOLID, NON-FERROUS BRASS OR ALUMINUM
- THERMALLY FORMED ACRYLIC RANGES FROM 3/16" TO 1/4" THICK, DEPENDING ON SIZE. VIRGIN WHITE ACRYLIC IS UV STABLE, AND ALL FAUX ACRYLIC COLORS ARE MIXED COMPLETELY THROUGH TO AVOID NOTICEABLE FADING
- WHITE ACRYLIC IS UL-94 HB FLAME CLASS RATING
- OCL METAL FINISHES ARE APPLIED BY HAND AND RECEIVE A PROTECTIVE CLEAR COAT



**CATALOG CODES**

<b>MN1</b>	-	<b>B</b>	-	<b>C</b>	-	<b>E</b>	-	<b>F</b>	-	<b>H</b>	-	<b>I</b>	-	<b>J</b>
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		OPTIONS

SPECIFY CATALOG CODE		A	B	C	D	E
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH		
<p><b>MN1</b> MONACO</p>	<b>PIAH</b> PENDANT WITH 3 ANGLED STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY  <b>PIED</b> PENDANT WITH 3 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY	<b>23</b>  <b>30</b>  <b>36</b>  <b>42</b>	<b>GW</b> GLOSS WHITE ACRYLIC  <b>PREMIUM ACRYLIC</b> <b>MW</b> MATTE WHITE ACRYLIC <b>FA</b> FAUX ALABASTER ACRYLIC <b>WS</b> WHITE SWIRL ACRYLIC	<b>POWDER COAT FINISHES</b> <b>BKP</b> BLACK <b>BMP</b> BRASS METALLIC <b>BNP</b> BRONZE <b>BTP</b> BLACK TEXTURED <b>GRP</b> GRAPHITE <b>GLP</b> GOLDTASTIC <b>MWP</b> MATTE WHITE <b>SGP</b> STEEL GRAY <b>SMP</b> SILVER METALLIC <b>SWP</b> SKY WHITE <b>WTP</b> WHITE TEXTURED	<b>PREMIUM METAL FINISHES</b> <b>PAL</b> POLISHED ALUMINUM <b>BAL</b> BRUSHED ALUMINUM <b>PTR</b> PEWTER <b>PBR</b> POLISHED BRASS <b>BBR</b> BRUSHED BRASS <b>ABR</b> ANTIQUE BRASS <b>STB</b> STATUARY BRONZE <b>SNK</b> SATIN NICKEL <b>ORB</b> OIL RUBBED BRONZE	

F		G	H	I	J
LIGHT SOURCE		VOLTAGE	OAH	CONTROL	OPTIONS
<b>LED OUTPUT</b> <b>LED1</b> <b>LED2</b>  <b>NOTE:</b> TOP LENS STANDARD IN LED	<b>COLOR TEMP</b> <b>27K</b> <b>30K</b> <b>35K</b> <b>40K</b>	<b>UNV</b> 120-277	<b>SPECIFY IN INCHES</b>	<b>DM1</b> 0-10V DIMMING 1%	<b>MOD</b> MODIFIED LUMINAIRE (CONTACT LOCAL REP)
<b>3INI50</b> 3 - E26 MEDIUM BASE SOCKET - A19 LAMP (23") 150W MAX INC PER LAMP (BY OTHERS)  <b>6INI50</b> 6 - E26 MEDIUM BASE SOCKET - A19 LAMP (30", 36") 150W MAX INC PER LAMP (BY OTHERS)  <b>8INI50</b> 8 - E26 MEDIUM BASE SOCKET - A19 LAMP (42") 150W MAX INC PER LAMP (BY OTHERS)	<b>LEAVE BLANK FOR SCREW IN</b>	<b>120V</b> (SCREW IN ONLY)		<b>LEAVE BLANK FOR SCREW IN</b>	

SAMPLE CODE: MN1-PIED-36-MW-BAL-LED1/35K-UNV-48-DM1

**MODS, NOTES, & COMMENTS**

LUMENS AND WATTAGE CHART		23	30	36	42
<b>LED1</b>	LUMENS DELIVERED	4500	4500	4500	4500
	SYSTEM WATTAGE	50	50	50	50
<b>LED2</b>	LUMENS DELIVERED	9100	9100	9100	9100
	SYSTEM WATTAGE	105	105	105	105

This chart was created for a 35K color temp with standard white acrylic. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. LED wattage and lumen data approx. pending LM-79 testing.