



Monaco™

SCONCE


FEATURES

- THE MONACO FEATURES A SHALLOW ACRYLIC DIFFUSER ACCENTED BY A ROLLED BRASS OR ALUMINUM RING; ITS TRANSITIONAL DESIGN MAKES THE MONACO A WELCOME PIECE FOR BOTH CONTEMPORARY AND TRADITIONAL APPLICATIONS
- CONSTRUCTED WITH SOLID, NON-FERROUS BRASS OR ALUMINUM
- THERMALLY FORMED ACRYLIC RANGES FROM 3/16" TO 1/4" THICK, DEPENDING ON SIZE. VIRGIN WHITE ACRYLIC IS UV STABLE, AND ALL FAUX ACRYLIC COLORS ARE MIXED COMPLETELY THROUGH TO AVOID NOTICEABLE FADING
- WHITE ACRYLIC IS UL-94 HB FLAME CLASS RATING
- OCL METAL FINISHES ARE APPLIED BY HAND AND RECEIVE A PROTECTIVE CLEAR COAT



CATALOG CODES

MN1	-	S1SA	-	C	-	D	-	E	-	F	-	G	-	H	-	I
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS

SPECIFY CATALOG CODE		A	B	C	D	E	
		SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	
		S1SA	INDOOR ADA COMPLIANT SCONCE	13	GW GLOSS WHITE ACRYLIC	POWDER COAT FINISHES	
MN1 MONACO				16	PREMIUM ACRYLIC	PREMIUM METAL FINISHES	
					MW MATTE WHITE ACRYLIC	BKP BLACK	PAL POLISHED ALUMINUM
					FA FAUX ALABASTER ACRYLIC	BMP BRASS METALLIC	BAL BRUSHED ALUMINUM
					WS WHITE SWIRL ACRYLIC	BNP BRONZE	PTR PEWTER
						BTP BLACK TEXTURED	PBR POLISHED BRASS
						GRP GRAPHITE	BBR BRUSHED BRASS
						GLP GOLDTASTIC	ABR ANTIQUE BRASS
						MWP MATTE WHITE	STB STATUARY BRONZE
						SGP STEEL GRAY	SNK SATIN NICKEL
						SMP SILVER METALLIC	ORB OIL RUBBED BRONZE
						SWP SKY WHITE	
						WTP WHITE TEXTURED	

F		G	H	I
LIGHT SOURCE		VOLTAGE	CONTROL	OPTIONS
LED OUTPUT LED1	COLOR TEMP	UNV 120-277	DM1 0-10V DIMMING 1%	MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP)
NOTE: TOP LENS STANDARD IN LED	27K 30K 35K 40K			
SCREW IN OUTPUT	LEAVE BLANK FOR SCREW IN	120V (SCREW IN ONLY)	LEAVE BLANK FOR SCREW IN	
2IN40 2 - E12 BASE SOCKET - B10 LAMP 40W MAX INC PER LAMP (BY OTHERS)				

SAMPLE CODE: MN1-S1SA-13-MW-SNK-LED1/27K-UNV-DM1

MODS, NOTES, & COMMENTS

LUMENS AND WATTAGE CHART		
	13	16
LED1	LUMENS DELIVERED 1125	1125
	SYSTEM WATTAGE 15	15

This chart was created for a 35K color temp with standard white acrylic. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. LED wattage and lumen data approx. pending LM-79 testing.