



# Allure™

SCONCE/OUTDOOR

**FEATURES**

- THE ALLURE SCONCE FEATURES SOLID ALUMINUM DIE-CAST ENDS WITH A DOMED TOP
- 0.125" THICK ALUMINUM EXTRUDED BACK CHANNEL
- DECORATIVE ALUMINUM DIE-CAST HORIZONTAL BARS WITH DISTINCTIVE TAPERING ARCH DESIGN
- 3/16" THICK EXTRUDED VIRGIN WHITE ACRYLIC IS 45% DR HIGH IMPACT, UV STABLE, F1 RATED, AND UL-94 HB FLAME CLASS RATED
- ALLURE CAN BE MOUNTED VERTICALLY OR HORIZONTALLY
- HINGED FRONT FACE SIMPLIFIES MAINTENANCE



**CATALOG CODES**

<b>AU1</b>	-	<b>B</b>	-	<b>C</b>	-	<b>D</b>	-	<b>E</b>	-	<b>F</b>	-	<b>UNV</b>	-	<b>DM1</b>	-	<b>I</b>
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS

**SPECIFY CATALOG CODE**

A		B		C	D		E	
SERIES		HANGING SYSTEM		SIZE	DIFFUSER		FINISH	
 <b>AU1</b> ALLURE	<b>S1SA</b>	INDOOR ADA COMPLIANT SCONCE		<b>18</b>	<b>GW</b> GLOSS WHITE ACRYLIC <b>NOTE: REQUIRED FOR 010A</b>	<b>POWDER COAT FINISHES</b> <b>BKP</b> BLACK <b>BMP</b> BRASS METALLIC <b>BNP</b> BRONZE <b>BTP</b> BLACK TEXTURED <b>GRP</b> GRAPHITE <b>GLP</b> GOLDTASTIC <b>MWP</b> MATTE WHITE <b>SGP</b> STEEL GRAY <b>SMP</b> SILVER METALLIC <b>SWP</b> SKY WHITE <b>WTP</b> WHITE TEXTURED		
	<b>010A</b>	OUTDOOR ADA COMPLIANT SCONCE		<b>24</b>				
				<b>36</b>	<b>MW</b> MATTE WHITE ACRYLIC			
				<b>48</b>				

  

F		G		H		I	
LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS	
<b>LED OUTPUT</b> <b>LED1</b> <b>LED2</b>	<b>COLOR TEMP</b> <b>27K</b> <b>30K</b> <b>35K</b> <b>40K</b>	<b>UNV</b>	120-277	<b>DM1</b>	0-10V DIMMING 1%	<b>ULD</b>	DAMP LABEL ( <b>S1SA</b> ONLY)
						<b>BIOS</b>	BIOS SKYBLUE™ OR BIOS SKYBLUE™ DYNAMIC LIGHT ENGINE*
						<b>MOD</b>	MODIFIED LUMINAIRE (CONTACT LOCAL REP)

**SAMPLE CODE: AU1-S1SA-24-GW-WTP-LED1/27K-UNV-DM1**

\*Contact factory for **BIOS SkyBlue**® or **BIOS SkyBlue**® Dynamic light engine and control options. Visit [ocl.com/BIOS](http://ocl.com/BIOS) for more information.

UP TO **58** LM/W

LUMENS AND WATTAGE CHART					
		18"	24"	36"	48"
<b>LED1</b>	LUMENS DELIVERED	1050	1600	2600	3700
	SYSTEM WATTAGE	20	30	45	65
<b>LED2</b>	LUMENS DELIVERED	1350	2000	3250	4600
	SYSTEM WATTAGE	25	35	60	80

This chart was created for a 35K color temp. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. Wattage and lumen data approx. pending LM-79 testing.

**MODS, NOTES, & COMMENTS**