




Cirque™

PENDANT



> FEATURES

- Spun aluminum fixture housing.
- Bottom diffuser is virgin white acrylic, UV stable and UL-94 HB flame rated.
- Up to 70 lumens per watt.
- Field replacement of LED arrays and drivers is simple and requires minimal effort.
- LED luminaire reliability; L70 >70,000 hours at 70% lumen maintenance.
- 3 step MacAdam ellipse color binning.
- OCL metal finishes are applied by hand and receive a protective, clear coat lacquer.
- 24 standard powder coat paints offered, however all RAL colors available.
- Utilizes highly efficient, long lasting and low mercury T5 or T5HO lamps for minimal fixture maintenance and lamp disposal.
- Contact factory for additional modifications or options.

> MEASUREMENTS



CQ1-P1EC-38-GW-MWP

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
 CQ1	P1EC PENDANT WITH 3 ANGLED AIRCRAFT CABLES AND A WHITE POWER CORD TO CANOPY 	26	GW GLOSS WHITE ACRYLIC MW MATTE WHITE ACRYLIC	PREMIUM METAL FINISH BAL BRUSHED ALUMINUM POWDER COAT FINISH PTD PAINTED - SPECIFY CODE [EX. BKP FOR BLACK PAINT, SEE PAGE 122 FOR PAINT OPTIONS]	26" 4LF14 4@14W T5 4LF24 4@24W T5HO (17454) 1LD58/30K 1@58W LED 3000K 1LD58/35K 1@58W LED 3500K (17449) 1LD58/40K 1@58W LED 4000K 1LD71/30K 1@71W LED 3000K 1LD71/35K 1@71W LED 3500K (17448) 1LD71/40K 1@71W LED 4000K	120 277 347 (CFL ONLY)	32	DMD 0-10V DIMMING DRIVER (LED ONLY) DMA ADVANCE® MARK 10 DIMMING (CFL ONLY) DMA7 ADVANCE® MARK 7 DIMMING (CFL ONLY) DML LUTRON® DIMMING (CFL ONLY) EMI INTEGRAL EMERGENCY (CFL ONLY) ULD UL DAMP LABEL FUS FUSED
		38		38" 6LF14 6@14W T5 6LF24 6@24W T5HO (17455) 1LD109/30K 1@109W LED 3000K 1LD109/35K 1@109W LED 3500K (17451) 1LD109/40K 1@109W LED 4000K 1LD134/30K 1@134W LED 3000K 1LD134/35K 1@134W LED 3500K (17450) 1LD134/40K 1@134W LED 4000K		40		
		50		50" 6LF21/4LF14 6@21W T5 & 4@14W T5 6LF39/4LF24 6@39W T5HO & 4@24W T5HO (17456) 1LD185/30K 1@185W LED 3000K 1LD185/35K 1@185W LED 3500K (17453) 1LD185/40K 1@185W LED 4000K 1LD230/30K 1@230W LED 3000K 1LD230/35K 1@230W LED 3500K (17452) 1LD230/40K 1@230W LED 4000K		48		
✓ SPECIFY CATALOG CODE								
SAMPLE CODE: CQ1-P1EC-38-GW-MWP-6LF24-120-32					▲ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM			

> **FIXTURE SPECIFICATIONS**

- Fixture mounts to a standard 4" octagon J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballast available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year warranty depending on ballast specification).
- Integral Class II driver (3-5 year warranty depending on driver specification).
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 124-131 in the reference section.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.