

# Duo™

PENDANT

## FEATURES


- SIMPLE, LINEAR PROFILE CAN BE CONNECTED TO CREATE LONG, CONTINUOUS RUNS
- FIELD REPLACEMENT OF LED ARRAYS AND DRIVERS IS SIMPLE AND REQUIRES MINIMAL EFFORT
- FULLY ILLUMINATED "L", "T" OR "X" JUNCTIONS AVAILABLE TO CREATE SPECIAL INSTALLATIONS
- EXTRUDED DIFFUSER IS FROSTED WHITE ACRYLIC
- 3 STEP COLOR BINNING



### CATALOG CODES

<b>DO1</b>	-	<b>P1EB</b>	-	<b>C</b>	-	<b>MW</b>	-	<b>E</b>	-	<b>UNV</b>	-	<b>H</b>	-	<b>DM1</b>	-	<b>J</b>		
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		OAH		CONTROL		OPTIONS

### SPECIFY CATALOG CODE

A		B		C	D	E	
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH			
 DO1 DUO	<b>P1EB</b> PENDANT WITH AN AIRCRAFT CABLE ON EACH END OF THE FIXTURE AND A POWER CORD ON ONE END	<b>24</b> <b>36</b> <b>48</b> <b>60</b> <b>89</b> <b>XX*</b>	<b>MW</b> MATTE WHITE	<b>POWDER COAT FINISHES</b> <b>BKP</b> BLACK <b>BMP</b> BRASS METALLIC <b>BNP</b> BRONZE <b>BTP</b> BLACK TEXTURED <b>GRP</b> GRAPHITE <b>GLP</b> GOLDTASTIC  <b>PREMIUM METAL FINISHES</b> <b>BAL</b> BRUSHED ALUMINUM	<b>MWP</b> MATTE WHITE <b>SGP</b> STEEL GRAY <b>SMP</b> SILVER METALLIC <b>SWP</b> SKY WHITE <b>WTP</b> WHITE TEXTURED		

F		G	H	I	J
LIGHT SOURCE		VOLTAGE	OAH	CONTROL	OPTIONS
<b>LED OUTPUT</b> <b>2LED1</b> <b>2LED2</b>	<b>COLOR TEMP</b> <b>27K</b> <b>30K</b> <b>35K</b> <b>40K</b>	<b>UNV</b> 120-277	<b>48</b> <b>100</b> <b>144</b>	<b>DM1</b> 0-10V DIMMING 1%	<b>ULD</b> DAMP LABEL <b>BIOS</b> BIOS SKYBLUE™ OR BIOS SKLYBLUE™ DYNAMIC LIGHT ENGINE*** <b>IJL</b> ILLUMINATED "L" JUNCTION <b>IJT</b> ILLUMINATED "T" JUNCTION <b>IJX</b> ILLUMINATED "X" JUNCTION <b>MOD</b> MODIFIED LUMINAIRE (CONTACT LOCAL REP)

**SAMPLE CODE: DO1-P1EB-24-MW-WTP-2LED1/27K-UNV-48-DM1**

\*For a modified length, type in length of fixture in inches to the nearest 0.0625"; Min. 24"

\*\*For Minimum OAH, see hanging systems details. P1EB will ship with one of three standard OAH's (48", 100" or 144") field adjustable to the desired height

\*\*\*Contact factory for BIOS SkyBlue® or BIOS SkyBlue® Dynamic light engine and control options. Visit [ocl.com/BIOS](http://ocl.com/BIOS) for more information.

UP TO **63** LM/W

### LUMENS AND WATTAGE CHART

		28"	36"	48"	60"	89"
<b>2LED1</b>	LUMENS DELIVERED	1760	2640	3520	4400	7040
	SYSTEM WATTAGE	28	42	56	70	102
<b>2LED2</b>	LUMENS DELIVERED	2650	3900	5290	6550	9700
	SYSTEM WATTAGE	42	62	84	104	154

This chart was created for a 35K color temp. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. Wattage and lumen data approx. pending LM-79 testing.

### MODS, NOTES, & COMMENTS



This product meets the material restrictions of Article 4 of the RoHS Directive (2011/65/EU), including Commission Delegated Directive 2015/863.