

Element™

CEILING/SCONCE/OUTDOOR


FEATURES

- THE ELEMENT FEATURES AN EXTRUDED ALUMINUM BACK CHANNEL 2.50" WIDE AND 0.125" THICK WITH A MATTE ANODIZED SURFACE
- FEATURES SOLID ALUMINUM DIE-CAST ENDS
- 3/16" THICK EXTRUDED VIRGIN WHITE ACRYLIC IS 45% DR HIGH IMPACT, UV STABLE, F1 RATED, AND UL-94 HB FLAME CLASS RATED
- ELEMENT CAN BE MOUNTED VERTICALLY OR HORIZONTALLY
- TAMPER-PROOF STAINLESS STEEL SCREWS AVAILABLE AS AN OPTION



CATALOG CODES

EL1	-	B	-	C	-	E	-	UNV	-	DM1	-	I
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		VOLTAGE		CONTROL		OPTIONS

SPECIFY CATALOG CODE														
A		B			C	D		E						
SERIES		HANGING SYSTEM			SIZE	DIFFUSER		FINISH						
 EL1 ELEMENT		S1SA	INDOOR ADA COMPLIANT SCONCE			24	GW	GLOSS WHITE ACRYLIC NOTE: REQUIRED FOR 010A		POWDER COAT FINISHES BKP BLACK BMP BRASS METALLIC BNP BRONZE BTP BLACK TEXTURED GRP GRAPHITE GLP GOLDTASTIC MWP MATTE WHITE SGP STEEL GRAY SMP SILVER METALLIC SWP SKY WHITE WTP WHITE TEXTURED				
		C1NA	SURFACE CEILING MOUNT			36	MW	MATTE WHITE ACRYLIC						
		010A	OUTDOOR ADA COMPLIANT SCONCE			48								
						60								
F		G			H		I							
LIGHT SOURCE		VOLTAGE			CONTROL		OPTIONS							
LED OUTPUT	COLOR TEMP	UNV 120-277			DM1 0-10V DIMMING 1%		ULD DAMP LABEL SJB MOUNTING COVER FOR STANDARD 4" J-BOX TPS TAMPER PROOF SCREWS MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP)							
LED1	27K													
LED2	30K													
	35K													
	40K													

SAMPLE CODE: EL1-C1NA-24-GW-WTP-LED1/27K-UNV-DM1

UP TO **56** LM/W

LUMENS AND WATTAGE CHART					
		24"	36"	48"	60"
LED1	LUMENS DELIVERED	950	1450	2000	2500
	SYSTEM WATTAGE	15	25	35	40
LED2	LUMENS DELIVERED	1150	1800	2450	3100
	SYSTEM WATTAGE	20	30	40	55

This chart was created for a 35K color temp. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. Wattage and lumen data approx. pending LM-79 testing.

MODS, NOTES, & COMMENTS