

# Flux™

## SCONCE

### FEATURES


- THE FLUX SCONCE FEATURES A FULLY ENCLOSED VACUUM-FORMED ACRYLIC DIFFUSER AND HAS A BULBOUS SHAPE.
- THE FLUX FEATURES A FORMED SHEET METAL FACE FROM 0.064" THICK ALUMINUM.
- FLUX CAN BE MOUNTED VERTICALLY OR HORIZONTALLY.
- VIRGIN WHITE ACRYLIC IS UV STABLE AND UL-94 HB FLAME CLASS RATED.



### CATALOG CODES

<b>FX1</b>	-	<b>S1SA</b>	-	<b>18</b>	-	<b>MW</b>	-	<b>E</b>	-	<b>I</b>	-	<b>UNV</b>	-	<b>DM1</b>	-	<b>I</b>
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS

### SPECIFY CATALOG CODE

A		B		C	D		E		
SERIES		HANGING SYSTEM		SIZE	DIFFUSER		FINISH		
 <b>FX1</b> FLUX		<b>S1SA</b> INDOOR ADA COMPLIANT SCONCE		<b>18</b>	<b>MW</b> MATTE WHITE ACRYLIC		<b>POWDER COAT FINISHES</b> <b>BKP</b> BLACK <b>MWP</b> MATTE WHITE <b>BMP</b> BRASS METALLIC <b>SGP</b> STEEL GRAY <b>BNP</b> BRONZE <b>SMP</b> SILVER METALLIC <b>BTP</b> BLACK TEXTURED <b>SWP</b> SKY WHITE <b>GRP</b> GRAPHITE <b>WTP</b> WHITE TEXTURED <b>GLP</b> GOLDTASTIC		
<b>LED OUTPUT</b> <b>LED1</b>		<b>COLOR TEMP</b> <b>27K</b> <b>30K</b> <b>35K</b> <b>40K</b>		<b>UNV</b> 120-277		<b>DM1</b> 0-10V DIMMING 1%		<b>ULD</b> DAMP LABEL <b>BIOS</b> BIOS SKYBLUE™ OR BIOS SKYBLUE™ DYNAMIC LIGHT ENGINE* <b>MOD</b> MODIFIED LUMINAIRE (CONTACT LOCAL REP)	

SAMPLE CODE: FX1-S1SA-18-MW-WTP-LED1/27K-UNV-DM1

\*Contact factory for BIOS SkyBlue® or BIOS SkyBlue® Dynamic light engine and control options. Visit [ocl.com/BIOS](http://ocl.com/BIOS) for more information.

### LUMENS AND WATTAGE CHART

		18"
<b>LED1</b>	LUMENS DELIVERED	1750
	SYSTEM WATTAGE	25

This chart was created for a 35K color temp. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. Wattage and lumen data approx. pending LM-79 testing.

### MODS, NOTES, & COMMENTS