





Fiori™

CEILING

> FEATURES

- Field replacement for LED array and driver is simple and requires minimal effort.
- Excellent thermal management is achieved through an extruded and machined aluminum fixture body.
- LED luminaire reliability, L70 >100,000 hours at 70% lumen maintenance.
- 45° cutoff and stepped bezel minimizes glare and increases visual comfort.
- Numerous secondary lens options available.
- Fixture and LED light source are tested to LM-79 standards.
- 3 step MacAdam ellipse color binning and 84 CRI standard. 2 step binning and 90+ CRI available [contact factory for details].
- Varying beam spread options are available: Narrow Flood [24 degree] or Wide Flood [50 degree].
- 24 standard powder coat paints offered, however all RAL colors available.
- Contact factory for additional modifications or options.

> MEASUREMENTS








> MATCHING FIXTURES

- Pendant
- Sconce



Shown with 3" mud ring mounting.

FR2-C1NA-08-WF-BTP

SERIES	HANGING SYSTEM	SIZE	REFLECTOR	FINISH	LIGHT SOURCE		VOLTAGE	OPTIONS	
					LED OUTPUT	COLOR TEMP			
 FR2  FR3  FR4  FR1	C1NA SURFACE CEILING MOUNT 	08	NF NARROW FLOOD [24 DEGREE] WF WIDE FLOOD [50 DEGREE]	AWP AUTUMN WHITE PAINT BEP BEIGE PAINT BKP BLACK PAINT BLP BLUE PAINT BMP BRASS METALLIC PAINT BNP BRONZE PAINT BTP BLACK TEXTURED PAINT CHP COPPER HAMMERTONE PAINT CMP COPPER METALLIC PAINT DBP DENIM BLUE PAINT GRP GRAPHITE PAINT GTP GRAY TEXTURED PAINT HEP HENNA PAINT KAP KHAKI PAINT LBP LIGHT BRONZE PAINT MWP MATTE WHITE PAINT RHP RESEDA HAMMERTONE PAINT SAP SAGE GREEN PAINT SGP STEEL GRAY PAINT SHP SILVER HAMMERTONE PAINT SMP SILVER METALLIC PAINT SRP STORM GRAY PAINT SWP SKY WHITE PAINT WTP WHITE TEXTURED PAINT	LED OUTPUT	COLOR TEMP	UNV 120-277	DMO 0-10V DIMMING 10% DM1 0-10V DIMMING 1% (NOT AVAILABLE IN 8") DM3 LUTRON HI-LUME ECOSYSTEM 1% (NOT AVAILABLE IN 8") DM4 LUTRON HI-LUME 3-WIRE 1% (NOT AVAILABLE IN 8") HCL HEX CELL LOUVER SFL SOFTENING LENS SPL SPREAD LENS LSL LINEAR SPREAD LENS	
					8"				LED1 LED2 LED3
				13"			LED1 LED2 LED3	27K 30K 35K 40K	
<p>✓ SPECIFY CATALOG CODE</p>									
<p>SAMPLE CODE: FR2-C1NA-08-WF-BTP-LED1/35K-UNV</p>					<p>▲ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM</p>				

> **FIXTURE SPECIFICATIONS**

- Fixture mounts to a standard 4" octagon J-box (supplied by others).
- Fixture is provided with 5" dia. cover plate finished to match the fixture body. If no visible cover plate is desired, a 3" mud ring should be pre-installed (supplied by others). 5" dia. cover plate can be discarded if unused.
- Fixture supplied with clear lens unless optional secondary lens specified.
- Various types of dimming drivers available, controls not included.
- Class II LED drivers - 120-277VAC 50/60Hz.
- Typical LED CRI 80+.
- For photometric data, please visit www.ocl.com.
- For specific mounting instructions, please contact factory.
- Five year product warranty.
- All specifications and information subject to change without notice. See submittal for current specifications and information.

> **LIGHT SOURCE PERFORMANCE CHART**

		SIZE	
		8"	13"
LED1	LUMENS DELIVERED	1500	1500
	SYSTEM WATTAGE	16	16
LED2	LUMENS DELIVERED	NA	2135
	SYSTEM WATTAGE	NA	26
LED3	LUMENS DELIVERED	NA	2855
	SYSTEM WATTAGE	NA	37