


HORIZON™ SCONCE




FIXTURE WEIGHT 5 LBS




FIXTURE WEIGHT 10 LBS



HR1-S1SA-16-GW-BAL



FIXTURE WEIGHT 5 LBS



FIXTURE WEIGHT 11 LBS



HR1-S1SB-16-WS-ORB

MATCHING FIXTURES



page 60









page 450



page 486

FEATURES

- The Horizon features a low-profile, minimalist square trim.
- A transitional design makes it a welcome piece for both contemporary and traditional applications.
- Spun from solid, non-ferrous 0.040" thick brass or 0.064" thick aluminum.
- Thermally formed acrylic ranges from 3/16" to 1/4" thick, depending on size. Virgin white acrylic is UV stable, and all faux acrylic colors are mixed completely through to avoid noticeable fading.
- White acrylic is UL-94 HB Flame Class rated.
- OCL metal finishes are applied by hand and receive a protective clear coat lacquer.
- 21 standard powder coat paints offered, however all RAL colors available.
- Fixture offered with a variety of compact fluorescent and incandescent optic packages.
- Contact factory for additional modifications or options.

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OPTIONS
 <p>HR1</p>	<p>S15A INDOOR ADA COMPLIANT SCENCE</p> 	16	<p>GW GLOSS WHITE ACRYLIC</p> <p>MW MATTE WHITE ACRYLIC</p>	<p>PREMIUM METAL FINISH</p> <p>PAL POLISHED ALUMINUM</p> <p>BAL BRUSHED ALUMINUM</p> <p>PTR PEWTER</p>	<p>16" </p> <p>2QD13 2@13W QD (13793.0)</p> <p>2IN40 2@40W IN (13808.0)</p>	<p>120</p> <p>277</p> <p>347</p>	<p>DMA ADVANCE® DIMMING BALLAST</p> <p>DML LUTRON® DIMMING BALLAST</p> <p>EMR REMOTE MOUNT EMERGENCY</p> <p>FUS FUSED</p> <p>ULD UL DAMP LABEL</p> <p>TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)</p>
		26	<p>FA FAUX ALABASTER ACRYLIC</p> <p>NH NATURAL HORN ACRYLIC</p> <p>ET ETRUSCAN ACRYLIC</p> <p>WS WHITE SWIRL ACRYLIC</p>	<p>PBR POLISHED BRASS</p> <p>BBR BRUSHED BRASS</p> <p>ABR ANTIQUE BRASS</p> <p>STB STATUARY BRONZE</p> <p>SNK SATIN NICKEL</p> <p>ORB OIL RUBBED BRONZE</p> <p>POWDER COATED FINISH</p> <p>PTD PAINTED – SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>26" </p> <p>2BX27 2@27W BX</p> <p>2IN40 2@40W IN</p>		
 <p>HR1</p>	<p>S15B INDOOR SCENCE</p> 	16	<p>GW GLOSS WHITE ACRYLIC</p> <p>MW MATTE WHITE ACRYLIC</p>	<p>PREMIUM METAL FINISH</p> <p>PAL POLISHED ALUMINUM</p> <p>BAL BRUSHED ALUMINUM</p> <p>PTR PEWTER</p>	<p>16"</p> <p>2QD13 2@13W QD (13809.0)</p> <p>2IN60 2@60W IN</p>	<p>120</p> <p>277</p> <p>347</p>	<p>DMA ADVANCE® DIMMING BALLAST</p> <p>DML LUTRON® DIMMING BALLAST</p> <p>EMR REMOTE MOUNT EMERGENCY</p> <p>FUS FUSED</p> <p>ULD UL DAMP LABEL</p> <p>TLP TOP LENS PRISMATIC ACRYLIC (ONLY ON FLUORESCENT)</p>
		26	<p>FA FAUX ALABASTER ACRYLIC</p> <p>NH NATURAL HORN ACRYLIC</p> <p>ET ETRUSCAN ACRYLIC</p> <p>WS WHITE SWIRL ACRYLIC</p>	<p>PBR POLISHED BRASS</p> <p>BBR BRUSHED BRASS</p> <p>ABR ANTIQUE BRASS</p> <p>STB STATUARY BRONZE</p> <p>SNK SATIN NICKEL</p> <p>ORB OIL RUBBED BRONZE</p> <p>POWDER COATED FINISH</p> <p>PTD PAINTED – SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 492 FOR PAINT OPTIONS)</p>	<p>26"</p> <p>2QD26 2@26W QD (12201.0)</p> <p>2IN100 2@100W IN (13792.0)</p>		

▾ SPECIFY CATALOG CODE

SAMPLE CODE: **HR1-S15B-16-WS-ORB-2QD13-120-FUS**

↑ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM

- Fixture mounts to a standard 4" J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year ballast warranty depending on ballast specification).
- ADA compliant version available.
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 496-505 in the reference section.
- For specific mounting instructions, please contact factory.
- Five year product warranty.