



# Illusion™

SCENCE


**FEATURES**

- THE ILLUSION EPITOMIZES MINIMALIST DESIGN WITH ITS SIMPLE SHAPE AND MERE 2.50" PROJECTION FROM THE WALL
- 1.50" WIDE MATTE ANODIZED, ALUMINUM EXTRUDED BACK CHANNEL
- 5/32" THICK, EXTRUDED VIRGIN WHITE ACRYLIC DIFFUSER
- VERTICAL OR HORIZONTAL MOUNTING
- FIXTURE IS ADA COMPLIANT



**CATALOG CODES**

<b>IL1</b>	-	<b>S1SA</b>	-	<b>C</b>	-	<b>GW</b>	-	<b>E</b>	-	<b>f</b>	-	<b>UNV</b>	-	<b>DM1</b>	-	<b>I</b>
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS

SPECIFY CATALOG CODE		A	B	C	D	E	
		SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	
 <p><b>IL1</b> ILLUSION</p>	<b>S1SA</b>	INDOOR ADA COMPLIANT SCENCE		<b>24</b>	<b>GW</b> GLOSS WHITE ACRYLIC	<b>POWDER COAT FINISHES</b>	
				<b>36</b>		<b>BKP</b> BLACK	<b>MWP</b> MATTE WHITE
				<b>48</b>		<b>BMP</b> BRASS METALLIC	<b>SGP</b> STEEL GRAY
				<b>60</b>		<b>BNP</b> BRONZE	<b>SMP</b> SILVER METALLIC
						<b>BTP</b> BLACK TEXTURED	<b>SWP</b> SKY WHITE
						<b>GRP</b> GRAPHITE	<b>WTP</b> WHITE TEXTURED
						<b>GLP</b> GOLDTASTIC	
						<b>PREMIUM METAL FINISHES</b>	
						<b>BAL</b> BRUSHED ALUMINUM	

F		G	H	I
LIGHT SOURCE		VOLTAGE	CONTROL	OPTIONS
<b>LED OUTPUT</b>	<b>COLOR TEMP</b>	<b>UNV</b> 120-277	<b>DM1</b> 0-10V DIMMING 1%	<b>SJB</b> MOUNTING COVER FOR STANDARD 4" J-BOX <b>ULD</b> UL DAMP LABEL <b>BIOS</b> BIOS SKYBLUE™ OR BIOS SKLYBLUE™ DYNAMIC LIGHT ENGINE* <b>MOD</b> MODIFIED LUMINAIRE (CONTACT LOCAL REP)
<b>LED1</b>	<b>27K</b>			
<b>LED2</b>	<b>30K</b>			
	<b>35K</b>			
	<b>40K</b>			

**SAMPLE CODE: IL1-S1SA-24-GW-BAL-LED1/30K-UNV-DM1**

\*Contact factory for BIOS SkyBlue® or BIOS SkyBlue® Dynamic light engine and control options. Visit [ocl.com/BIOS](http://ocl.com/BIOS) for more information.

**MODS, NOTES, & COMMENTS**

UP TO **60** LM/W

**LUMENS AND WATTAGE CHART**

		24	36	48	60
<b>LED1</b>	LUMENS DELIVERED	1800	2800	3750	4750
	SYSTEM WATTAGE	30	50	65	85
<b>LED2</b>	LUMENS DELIVERED	2250	3450	4700	5950
	SYSTEM WATTAGE	40	60	85	105

This chart was created for a 35K color temp. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp.