



Intrigue™

SCONCE/OUTDOOR

FEATURES

- THE INTRIGUE SCONCE FEATURES SOLID ALUMINUM DIE-CAST ENDS WITH A DOMED TOP AND A DISTINCTIVE TAPERING ARCH DESIGN
- 0.125" THICK, MATTE ANODIZED, ALUMINUM EXTRUDED BACK CHANNEL
- FEATURES 1.0" WIDE BY 0.375" THICK EXTRUDED ALUMINUM FRONT BAR WITH OPTIONAL SLIT CUTOUT
- 3/16" THICK EXTRUDED VIRGIN WHITE ACRYLIC IS 45% DR HIGH IMPACT, UV STABLE, F1 RATED, AND UL-94 HB FLAME CLASS RATED
- INTRIGUE CAN BE MOUNTED VERTICALLY OR HORIZONTALLY
- HINGED FRONT FACE SIMPLIFIES MAINTENANCE



CATALOG CODES

A	B	C	D	E	F	UNV	DM1	I
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LIGHT SOURCE	VOLTAGE	CONTROL	OPTIONS

SPECIFY CATALOG CODE

A		B		C	D		E	
SERIES		HANGING SYSTEM		SIZE	DIFFUSER		FINISH	
 IN1 INTRIGUE	S1SA	INDOOR ADA COMPLIANT SCONCE		18	GW	GLOSS WHITE NOTE: REQUIRED FOR 010A		POWDER COAT FINISHES BKP BLACK BMP BRASS METALLIC BNP BRONZE BTP BLACK TEXTURED GRP GRAPHITE GLP GOLDTASTIC MWP MATTE WHITE SGP STEEL GRAY SMP SILVER METALLIC SWP SKY WHITE WTP WHITE TEXTURED
	010A	OUTDOOR ADA COMPLIANT SCONCE		24				
				36	MW	MATTE WHITE		
				48				
 IN2 INTRIGUE								
F		G		H		I		
LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS		
LED OUTPUT LED1 LED2	COLOR TEMP 27K 30K 35K 40K	UNV	120-277	DM1	0-10V DIMMING 1%		ULD DAMP LABEL (S1SA ONLY) BIOS BIOS SKYBLUE™ OR BIOS SKLYBLUE™ DYNAMIC LIGHT ENGINE* MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP)	

SAMPLE CODE: IN2-S1SA-24-GW-GRP-LED1/27K-UNV-DM1

*Contact factory for BIOS SkyBlue® or BIOS SkyBlue® Dynamic light engine and control options. Visit ocl.com/BIOS for more information.

UP TO **58** LM/W

LUMENS AND WATTAGE CHART

		18"	24"	36"	48"
LED1	LUMENS DELIVERED	1050	1600	2600	3700
	SYSTEM WATTAGE	20	30	45	65
LED2	LUMENS DELIVERED	1350	2000	3250	4600
	SYSTEM WATTAGE	25	35	60	80

This chart was created for a 35K color temp. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. Wattage and lumen data approx. pending LM-79 testing.

MODS, NOTES, & COMMENTS