



Regency™

SCONCE

FEATURES

- THE REGENCY SCONCE IS A ROBUST AND STYLISH WALL FIXTURE CONSTRUCTED WITH SOLID ALUMINUM OR BRASS BAR STOCK
- 1/8" THICK EXTRUDED, VIRGIN WHITE ACRYLIC DIFFUSER IS UV STABLE AND UL-94 HB FLAME CLASS RATED
- FAUX ACRYLIC IS THERMALLY FORMED AND COLORS ARE MIXED COMPLETELY THROUGH TO AVOID NOTICEABLE FADING



CATALOG CODES

RG1	-	S1SA	-	C	-	D	-	E	-	/	-	UNV	-	DM1	-	I
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS

SPECIFY CATALOG CODE

A		B		C		D		E			
SERIES		HANGING SYSTEM*		SIZE		DIFFUSER		FINISH			
 RG1 REGENCY		S1SA	INDOOR ADA COMPLIANT SCONCE	18	GW	GLOSS WHITE		POWDER COAT FINISHES			
				24	MW	MATTE WHITE		BKP	BLACK	PREMIUM METAL FINISH	
					FA	FAUX ALABASTER		BMP	BRASS METALLIC	BAL	BRUSHED ALUMINUM
					WS	WHITE SWIRL		BNP	BRONZE	PTR	PEWTER
								BTP	BLACK TEXTURED	PBR	POLISHED BRASS
								GRP	GRAPHITE	BBR	BRUSHED BRASS
								GLP	GOLDTASTIC	ABR	ANTIQUÉ BRASS
								MWP	MATTE WHITE	STB	STATUARY BRONZE
								SGP	STEEL GRAY	SNK	SATIN NICKEL
								SMP	SILVER METALLIC	ORB	OIL RUBBED BRONZE
								SWP	SKY WHITE		
								WTP	WHITE TEXTURED		

F		G		H		I	
LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS	
LED OUTPUT	COLOR TEMP	UNV	120-277	DM1	0-10V DIMMING 1%	ULD	DAMP LABEL (S1SA ONLY)
LED1	27K					BIOS	BIOS SKYBLUE™ OR BIOS SKLYBLUE™ DYNAMIC LIGHT ENGINE*
LED2	30K					MOD	MODIFIED LUMINAIRE (CONTACT LOCAL REP)
	35K						
	40K						

SAMPLE CODE: **RG1-S1SA-18-GW-BTP-LED1/27K-UNV-DM1**

*Contact factory for **BIOS SkyBlue®** or **BIOS SkyBlue® Dynamic** light engine and control options. Visit ocl.com/BIOS for more information.

UP TO **55** LM/W

LUMENS AND WATTAGE CHART		SIZE	
		18"	24"
LED1	LUMENS DELIVERED	1030	1280
	SYSTEM WATTAGE	20	25
LED2	LUMENS DELIVERED	1550	1940
	SYSTEM WATTAGE	30	35

This chart was created for a 35K color temp. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp.

MODS, NOTES, & COMMENTS