


Tiny™ PENDANT



> FEATURES

- Large scale spun aluminum shade.
- Concave bottom diffuser is virgin white acrylic, UV stable and UL-94 HB flame rated.
- Easy relamping with no tools or hardware removal.
- Up to 75 lumens per watt.
- Field replacement of LED arrays and drivers is simple and requires minimal effort.
- LED luminaire reliability; L70 >70,000 hours at 70% lumen maintenance.
- 3 step MacAdam ellipse color binning.
- OCL metal finishes are applied by hand and receive a protective, clear coat lacquer.
- 24 standard powder coat paints offered, however all RAL colors available.
- Contact factory for additional modifications or options.

> MEASUREMENTS



TN1-P1EC-40-GW-GRP

SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LAMPING (PHOTOMETRIC TEST #)	VOLTAGE	OAH SPECIFY IN INCHES	OPTIONS
 TN1	P1EC PENDANT WITH 3 ANGLED AIRCRAFT CABLES AND A WHITE POWER CORD TO CANOPY 	40	GW GLOSS WHITE ACRYLIC MW MATTE WHITE ACRYLIC	PREMIUM METAL FINISH BAL BRUSHED ALUMINUM POWDER COAT FINISH PTD PAINTED - SPECIFY CODE (EX. BKP FOR BLACK PAINT, SEE PAGE 122 FOR PAINT OPTIONS)	40" 4QD26 4@26W QD 4TT32 4@32W TT 4TT42 4@42W TT (17496) 4BX40 4@40W BX 1LD58/30K 1@58W LED 3000K 1LD58/35K 1@58W LED 3500K (17495) 1LD58/40K 1@58W LED 4000K 1LD71/30K 1@71W LED 3000K 1LD71/35K 1@71W LED 3500K (17494) 1LD71/40K 1@71W LED 4000K	120 277 347 (CFL ONLY)	50	DMO 0-10V DIMMING DRIVER (LED ONLY) DMA ADVANCE® MARK 10 DIMMING (CFL ONLY) DMA7 ADVANCE® MARK 7 DIMMING (CFL ONLY) DML LUTRON® DIMMING (CFL ONLY) EMI INTEGRAL EMERGENCY (CFL ONLY) ULD UL DAMP LABEL FUS FUSED
✓ SPECIFY CATALOG CODE								
SAMPLE CODE: TN1-P1EC-40-GW-GRP-4TT42-120-50					^ PHOTOMETRIC INFORMATION AVAILABLE AT WWW.OCL.COM			

> **FIXTURE SPECIFICATIONS**

- Fixture mounts to a standard 4" octagon J-box (supplied by others).
- Bodine® emergency ballast available, standard with remote mounted test switch and indicator light.
- Advance® and Lutron® dimming ballasts available. Controls not included.
- Integral HPF electronic fluorescent ballast with Class A sound rating (3-5 year warranty depending on ballast specification).
- Integral Class II driver (3-5 year warranty depending on driver specification).
- For photometric data, please visit www.ocl.com.
- For lamp and base information, see pages 124-131 in the reference section.
- Structural mounting required for fixtures over 50 lbs.
- For specific mounting instructions, please contact factory.
- Five year product warranty.