



Una™

CEILING

FEATURES

- SIMPLE, LINEAR 3"W X 3.5"H PROFILE CAN BE CONNECTED TO CREATE LONG, CONTINUOUS RUNS
- FIELD REPLACEMENT OF LED ARRAYS AND DRIVERS IS SIMPLE AND REQUIRES MINIMAL EFFORT
- QUALITY CONSTRUCTION INCLUDES HEAVY GAUGE SHEET METAL, EXTRUDED ALUMINUM, DIE-CAST ALUMINUM, AND EXTRUDED ACRYLIC
- EXTRUDED DIFFUSER IS FROSTED WHITE ACRYLIC, UV STABLE AND UL-94 HB FLAME RATED
- 3 STEP COLOR BINNING



CATALOG CODES

| | | | | | | | | | | | | | | | | |
|------------|---|----------------|---|----------|---|-----------|---|----------|---|--------------|---|------------|---|------------|---|----------|
| UA1 | - | C1NA | - | C | - | MW | - | E | - | I | - | UNV | - | DM1 | - | I |
| SERIES | | HANGING SYSTEM | | SIZE | | DIFFUSER | | FINISH | | LIGHT SOURCE | | VOLTAGE | | CONTROL | | OPTIONS |

| SPECIFY CATALOG CODE | | | | | |
|----------------------|----------------|-----------------------|--|-----------------------|--|
| A | B | | C | D | E |
| SERIES | HANGING SYSTEM | | SIZE | DIFFUSER | FINISH |
| UA1 UNA | C1NA | SURFACE CEILING MOUNT | 24 36 48 60 89 XX | MW MATTE WHITE | POWDER COAT FINISHES BKP BLACK BMP BRASS METALLIC BNP BRONZE BTP BLACK TEXTURED GRP GRAPHITE GLP GOLDTASTIC PREMIUM METAL FINISHES BAL BRUSHED ALUMINUM MWP MATTE WHITE SGP STEEL GRAY SMP SILVER METALLIC SWP SKY WHITE WTP WHITE TEXTURED |

| F | | G | H | | I |
|---|---|--------------------|-----------------------------|---|---------|
| LIGHT SOURCE | | VOLTAGE | CONTROL | | OPTIONS |
| LED OUTPUT LED1 LED2 | COLOR TEMP 27K 30K 35K 40K | UNV 120-277 | DM1 0-10V DIMMING 1% | ULD DAMP LABEL BIOS BIOS SKYBLUE™ OR BIOS SKYBLUE™ DYNAMIC LIGHT ENGINE** MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP) | |

SAMPLE CODE: UA1-C1NA-24-MW-WTP-LED1/27K-UNV-48-DM1

*For a modified length, type in length of fixture in inches to the nearest 0.0625"; Min. 24
 **Contact factory for BIOS SkyBlue® or BIOS SkyBlue® Dynamic light engine and control options. Visit ocl.com/BIOS for more information.

UP TO **80** LM/W

| LUMENS AND WATTAGE CHART | | | | | | |
|--------------------------|------------------|------|------|------|------|------|
| | | 24" | 36" | 48" | 60" | 89" |
| LED1 | LUMENS DELIVERED | 1120 | 1680 | 2240 | 2800 | 4080 |
| | SYSTEM WATTAGE | 14 | 21 | 28 | 35 | 51 |
| LED2 | LUMENS DELIVERED | 1680 | 2480 | 3360 | 4160 | 6160 |
| | SYSTEM WATTAGE | 21 | 31 | 42 | 52 | 77 |

This chart was created for a 35K color temp. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. Wattage and lumen data approx. pending LM-79 testing.

MODS, NOTES, & COMMENTS



This product meets the material restrictions of Article 4 of the RoHS Directive (2011/65/EU), including Commission Delegated Directive 2015/863