



# Una™

CEILING

**FEATURES**


- SIMPLE, LINEAR 3"W X 3.5"H PROFILE CAN BE CONNECTED TO CREATE LONG, CONTINUOUS RUNS
- FIELD REPLACEMENT OF LED ARRAYS AND DRIVERS IS SIMPLE AND REQUIRES MINIMAL EFFORT
- QUALITY CONSTRUCTION INCLUDES HEAVY GAUGE SHEET METAL, EXTRUDED ALUMINUM, DIE-CAST ALUMINUM, AND EXTRUDED ACRYLIC
- EXTRUDED DIFFUSER IS FROSTED WHITE ACRYLIC, UV STABLE AND UL-94 HB FLAME RATED
- 3 STEP COLOR BINNING



**CATALOG CODES**

<b>UA1</b>	-	<b>C1NA</b>	-	<b>C</b>	-	<b>MW</b>	-	<b>E</b>	-	<b>I</b>	-	<b>UNV</b>	-	<b>DM1</b>	-	<b>I</b>
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS

**SPECIFY CATALOG CODE**

A	B	C	D	E													
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH													
 <b>UA1</b> UNA	<b>C1NA</b> SURFACE CEILING MOUNT	<b>24</b> <b>36</b> <b>48</b> <b>60</b> <b>89</b> <b>XX</b>	<b>MW</b> MATTE WHITE	<p><b>POWDER COAT FINISHES</b></p> <table border="0"> <tr> <td><b>BKP</b> BLACK</td> <td><b>MWP</b> MATTE WHITE</td> </tr> <tr> <td><b>BMP</b> BRASS METALLIC</td> <td><b>SGP</b> STEEL GRAY</td> </tr> <tr> <td><b>BNP</b> BRONZE</td> <td><b>SMP</b> SILVER METALLIC</td> </tr> <tr> <td><b>BTP</b> BLACK TEXTURED</td> <td><b>SWP</b> SKY WHITE</td> </tr> <tr> <td><b>GRP</b> GRAPHITE</td> <td><b>WTP</b> WHITE TEXTURED</td> </tr> <tr> <td><b>GLP</b> GOLDTASTIC</td> <td></td> </tr> </table> <p><b>PREMIUM METAL FINISHES</b></p> <table border="0"> <tr> <td><b>BAL</b> BRUSHED ALUMINUM</td> </tr> </table>	<b>BKP</b> BLACK	<b>MWP</b> MATTE WHITE	<b>BMP</b> BRASS METALLIC	<b>SGP</b> STEEL GRAY	<b>BNP</b> BRONZE	<b>SMP</b> SILVER METALLIC	<b>BTP</b> BLACK TEXTURED	<b>SWP</b> SKY WHITE	<b>GRP</b> GRAPHITE	<b>WTP</b> WHITE TEXTURED	<b>GLP</b> GOLDTASTIC		<b>BAL</b> BRUSHED ALUMINUM
<b>BKP</b> BLACK	<b>MWP</b> MATTE WHITE																
<b>BMP</b> BRASS METALLIC	<b>SGP</b> STEEL GRAY																
<b>BNP</b> BRONZE	<b>SMP</b> SILVER METALLIC																
<b>BTP</b> BLACK TEXTURED	<b>SWP</b> SKY WHITE																
<b>GRP</b> GRAPHITE	<b>WTP</b> WHITE TEXTURED																
<b>GLP</b> GOLDTASTIC																	
<b>BAL</b> BRUSHED ALUMINUM																	

F	G	H	I												
LIGHT SOURCE	VOLTAGE	CONTROL	OPTIONS												
<table border="0"> <tr> <td><b>LED OUTPUT</b></td> <td><b>COLOR TEMP</b></td> </tr> <tr> <td><b>LED1</b></td> <td><b>27K</b></td> </tr> <tr> <td><b>LED2</b></td> <td><b>30K</b></td> </tr> <tr> <td></td> <td><b>35K</b></td> </tr> <tr> <td></td> <td><b>40K</b></td> </tr> </table>	<b>LED OUTPUT</b>	<b>COLOR TEMP</b>	<b>LED1</b>	<b>27K</b>	<b>LED2</b>	<b>30K</b>		<b>35K</b>		<b>40K</b>	<b>UNV</b> 120-277	<b>DM1</b> 0-10V DIMMING 1%	<table border="0"> <tr> <td><b>ULD</b> DAMP LABEL</td> </tr> <tr> <td><b>MOD</b> MODIFIED LUMINAIRE (CONTACT LOCAL REP)</td> </tr> </table>	<b>ULD</b> DAMP LABEL	<b>MOD</b> MODIFIED LUMINAIRE (CONTACT LOCAL REP)
<b>LED OUTPUT</b>	<b>COLOR TEMP</b>														
<b>LED1</b>	<b>27K</b>														
<b>LED2</b>	<b>30K</b>														
	<b>35K</b>														
	<b>40K</b>														
<b>ULD</b> DAMP LABEL															
<b>MOD</b> MODIFIED LUMINAIRE (CONTACT LOCAL REP)															

SAMPLE CODE: UA1-C1NA-24-MW-WTP-LED1/27K-UNV-48-DM1

UP TO **80** LM/W

**LUMENS AND WATTAGE CHART**

		24"	36"	48"	60"	89"
<b>LED1</b>	LUMENS DELIVERED	1120	1680	2240	2800	4080
	SYSTEM WATTAGE	14	21	28	35	51
<b>LED2</b>	LUMENS DELIVERED	1680	2480	3360	4160	6160
	SYSTEM WATTAGE	21	31	42	52	77

This chart was created for a 35K color temp. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. Wattage and lumen data approx. pending LM-79 testing.

**MODS, NOTES, & COMMENTS**



This product meets the material restrictions of Article 4 of the RoHS Directive (2011/65/EU), including Commission Delegated Directive 2015/863