




# Una™

OUTDOOR

**FEATURES**

- SIMPLE, LINEAR PROFILE CREATES SOFT GRAZING EFFECT ON WALL SURFACE
- FIELD REPLACEMENT OF LED ARRAYS AND DRIVERS IS SIMPLE AND REQUIRES MINIMAL EFFORT
- HEAVY WALL ALUMINUM EXTRUDED PROFILE
- EXTRUDED DIFFUSER IS FROSTED WHITE ACRYLIC, UV STABLE AND UL-94 HB FLAME RATED
- 3 STEP COLOR BINNING



**CATALOG CODES**

<b>UA1</b>	-	<b>O10A</b>	-	<b>C</b>	-	<b>MW</b>	-	<b>E</b>	-	<b>F</b>	-	<b>UNV</b>	-	<b>DM1</b>	-	<b>I</b>
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS

SPECIFY CATALOG CODE		A	B	C	D	E	
		SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	
 <b>UA1</b> UNA	<b>O10A</b>	OUTDOOR ADA COMPLIANT SCONCE		<b>14</b> <b>24</b> <b>36</b> <b>48</b> <b>60</b> <b>89</b>	<b>MW</b> MATTE WHITE	<b>POWDER COAT FINISHES</b>	
		<b>NOTE:</b> ONLY AVAILABLE IN DOWNWARD ORIENTATION				<b>BKP</b> BLACK	<b>MWP</b> MATTE WHITE
		<b>BMP</b> BRASS METALLIC	<b>SGP</b> STEEL GRAY				
		<b>BNP</b> BRONZE	<b>SMP</b> SILVER METALLIC				
		<b>BTP</b> BLACK TEXTURED	<b>SWP</b> SKY WHITE				
<b>GRP</b> GRAPHITE	<b>WTP</b> WHITE TEXTURED						
<b>GLP</b> GOLDTASTIC							

F		G	H	I
LIGHT SOURCE		VOLTAGE	CONTROL	OPTIONS
<b>LED OUTPUT</b>	<b>COLOR TEMP</b>	<b>UNV</b> 120-277	<b>DM1</b> 0-10V DIMMING 1%	<b>BIOS</b> BIOS SKYBLUE™ OR BIOS SKLYBLUE™ DYNAMIC LIGHT ENGINE** <b>MOD</b> MODIFIED LUMINAIRE (CONTACT LOCAL REP)
<b>LED1</b>	<b>27K</b>			
<b>LED2</b>	<b>30K</b> <b>35K</b> <b>40K</b>			

SAMPLE CODE: UA1-O10A-24-MW-WTP-LED1/27K-UNV-DM1

\*For a modified length, type in length of fixture in inches to the nearest 0.0625"; Min. 24  
 \*\*Contact factory for BIOS SkyBlue® or BIOS SkyBlue® Dynamic light engine and control options. Visit [ocl.com/BIOS](http://ocl.com/BIOS) for more information.

UP TO 80

		LUMENS AND WATTAGE CHART					
		14"	24"	36"	48"	60"	89"
<b>LED1</b>	LUMENS DELIVERED	640	1120	1680	2240	2800	4080
	SYSTEM WATTAGE	8	14	21	28	35	51
<b>LED2</b>	LUMENS DELIVERED	960	1680	2480	3360	4160	6160
	SYSTEM WATTAGE	12	21	31	42	52	77

This chart was created for a 35K color temp. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. Wattage and lumen data approx. pending LM-79 testing.

**MODS, NOTES, & COMMENTS**



This product meets the material restrictions of Article 4 of the RoHS Directive (2011/65/EU), including Commission Delegated Directive 2015/863