




Una™

OUTDOOR

FEATURES

- SIMPLE, LINEAR PROFILE CREATES SOFT GRAZING EFFECT ON WALL SURFACE
- FIELD REPLACEMENT OF LED ARRAYS AND DRIVERS IS SIMPLE AND REQUIRES MINIMAL EFFORT
- HEAVY WALL ALUMINUM EXTRUDED PROFILE
- EXTRUDED DIFFUSER IS FROSTED WHITE ACRYLIC, UV STABLE AND UL-94 HB FLAME RATED
- 3 STEP COLOR BINNING



CATALOG CODES

| | | | | | | | | | | | | | | | | |
|------------|---|----------------|---|----------|---|-----------|---|----------|---|--------------|---|------------|---|------------|---|----------|
| UA1 | - | O10A | - | C | - | MW | - | E | - | I | - | UNV | - | DM1 | - | I |
| SERIES | | HANGING SYSTEM | | SIZE | | DIFFUSER | | FINISH | | LIGHT SOURCE | | VOLTAGE | | CONTROL | | OPTIONS |

SPECIFY CATALOG CODE

| A | | B | | C | D | E | | | | | | | | | | | | | |
|-----------------------|--|---|--|---------------------------|-----------------------|---|--|----------------------------|------------------------|---------------------------|-----------------------|-------------------|----------------------------|---------------------------|----------------------|---------------------|---------------------------|-----------------------|--|
| SERIES | | HANGING SYSTEM | | SIZE | DIFFUSER | FINISH | | | | | | | | | | | | | |
| UA1 UNA | | O10A OUTDOOR ADA COMPLIANT SCONCE NOTE: ONLY AVAILABLE IN DOWNWARD ORIENTATION | | 14 | MW MATTE WHITE | POWDER COAT FINISHES <table border="0"> <tr> <td>BKP BLACK</td> <td>MWP MATTE WHITE</td> </tr> <tr> <td>BMP BRASS METALLIC</td> <td>SGP STEEL GRAY</td> </tr> <tr> <td>BNP BRONZE</td> <td>SMP SILVER METALLIC</td> </tr> <tr> <td>BTP BLACK TEXTURED</td> <td>SWP SKY WHITE</td> </tr> <tr> <td>GRP GRAPHITE</td> <td>WTP WHITE TEXTURED</td> </tr> <tr> <td>GLP GOLDTASTIC</td> <td></td> </tr> </table> | | BKP BLACK | MWP MATTE WHITE | BMP BRASS METALLIC | SGP STEEL GRAY | BNP BRONZE | SMP SILVER METALLIC | BTP BLACK TEXTURED | SWP SKY WHITE | GRP GRAPHITE | WTP WHITE TEXTURED | GLP GOLDTASTIC | |
| | | | | BKP BLACK | | | | MWP MATTE WHITE | | | | | | | | | | | |
| | | | | BMP BRASS METALLIC | | | | SGP STEEL GRAY | | | | | | | | | | | |
| | | | | BNP BRONZE | | | | SMP SILVER METALLIC | | | | | | | | | | | |
| | | | | BTP BLACK TEXTURED | | | | SWP SKY WHITE | | | | | | | | | | | |
| | | | | GRP GRAPHITE | | | | WTP WHITE TEXTURED | | | | | | | | | | | |
| GLP GOLDTASTIC | | | | | | | | | | | | | | | | | | | |
| 24 | | | | | | | | | | | | | | | | | | | |
| 36 | | | | | | | | | | | | | | | | | | | |
| 48 | | | | | | | | | | | | | | | | | | | |
| 60 | | | | | | | | | | | | | | | | | | | |
| 89 | | | | | | | | | | | | | | | | | | | |

| F | | G | H | I |
|---|---|--------------------|-----------------------------|---|
| LIGHT SOURCE | | VOLTAGE | CONTROL | OPTIONS |
| LED OUTPUT LED1 LED2 | COLOR TEMP 27K 30K 35K 40K | UNV 120-277 | DM1 0-10V DIMMING 1% | MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP) |

SAMPLE CODE: UA1-O10A-24-MW-WTP-LED1/27K-UNV-DM1

*For a modified length, type in length of fixture in inches to the nearest 0.0625"; Min. 24

UP TO 80

| | | 14" | 24" | 36" | 48" | 60" | 89" |
|-------------|------------------|-----|------|------|------|------|------|
| LED1 | LUMENS DELIVERED | 640 | 1120 | 1680 | 2240 | 2800 | 4080 |
| | SYSTEM WATTAGE | 8 | 14 | 21 | 28 | 35 | 51 |
| LED2 | LUMENS DELIVERED | 960 | 1680 | 2480 | 3360 | 4160 | 6160 |
| | SYSTEM WATTAGE | 12 | 21 | 31 | 42 | 52 | 77 |

This chart was created for a 35K color temp. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. Wattage and lumen data approx. pending LM-79 testing.

MODS, NOTES, & COMMENTS



This product meets the material restrictions of Article 4 of the RoHS Directive (2011/65/EU), including Commission Delegated Directive 2015/863