



# Una™

PENDANT

**FEATURES**

- SIMPLE, LINEAR 3"W X 3.5"H PROFILE CAN BE CONNECTED TO CREATE LONG, CONTINUOUS RUNS
- FIELD REPLACEMENT OF LED ARRAYS AND DRIVERS IS SIMPLE AND REQUIRES MINIMAL EFFORT
- QUALITY CONSTRUCTION INCLUDES HEAVY GAUGE SHEET METAL, EXTRUDED ALUMINUM, DIE-CAST ALUMINUM, AND EXTRUDED ACRYLIC
- EXTRUDED DIFFUSER IS FROSTED WHITE ACRYLIC, UV STABLE AND UL-94 HB FLAME RATED
- 3 STEP COLOR BINNING



**CATALOG CODES**

<b>UA1</b>	<b>P1EB</b>	<b>C</b>	<b>MW</b>	<b>E</b>	<b>F</b>	<b>UNV</b>	<b>H</b>	<b>DM1</b>	<b>J</b>
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LIGHT SOURCE	VOLTAGE	OAH	CONTROL	OPTIONS

SPECIFY CATALOG CODE																
A	B	C	D	E												
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH												
 <b>UA1</b> UNA	<b>P1EB</b> PENDANT WITH AN AIRCRAFT CABLE ON EACH END OF THE FIXTURE AND A POWER CORD ON ONE END	24 36 48 60 89 XX	<b>MW</b> MATTE WHITE	<b>POWDER COAT FINISHES</b> <table border="0"> <tr> <td><b>BKP</b> BLACK</td> <td><b>MWP</b> MATTE WHITE</td> </tr> <tr> <td><b>BMP</b> BRASS METALLIC</td> <td><b>SGP</b> STEEL GRAY</td> </tr> <tr> <td><b>BNP</b> BRONZE</td> <td><b>SMP</b> SILVER METALLIC</td> </tr> <tr> <td><b>BTP</b> BLACK TEXTURED</td> <td><b>SWP</b> SKY WHITE</td> </tr> <tr> <td><b>GRP</b> GRAPHITE</td> <td><b>WTP</b> WHITE TEXTURED</td> </tr> <tr> <td><b>GLP</b> GOLDTASTIC</td> <td></td> </tr> </table> <b>PREMIUM METAL FINISHES</b> <b>BAL</b> BRUSHED ALUMINUM	<b>BKP</b> BLACK	<b>MWP</b> MATTE WHITE	<b>BMP</b> BRASS METALLIC	<b>SGP</b> STEEL GRAY	<b>BNP</b> BRONZE	<b>SMP</b> SILVER METALLIC	<b>BTP</b> BLACK TEXTURED	<b>SWP</b> SKY WHITE	<b>GRP</b> GRAPHITE	<b>WTP</b> WHITE TEXTURED	<b>GLP</b> GOLDTASTIC	
<b>BKP</b> BLACK	<b>MWP</b> MATTE WHITE															
<b>BMP</b> BRASS METALLIC	<b>SGP</b> STEEL GRAY															
<b>BNP</b> BRONZE	<b>SMP</b> SILVER METALLIC															
<b>BTP</b> BLACK TEXTURED	<b>SWP</b> SKY WHITE															
<b>GRP</b> GRAPHITE	<b>WTP</b> WHITE TEXTURED															
<b>GLP</b> GOLDTASTIC																

F		G	H	I	J
LIGHT SOURCE		VOLTAGE	OAH*	CONTROL	OPTIONS
<b>LED OUTPUT</b> LED1 LED2	<b>COLOR TEMP</b> 27K 30K 35K 40K	<b>UNV</b> 120-277	48 100 144	<b>DM1</b> 0-10V DIMMING 1%	<b>ULD</b> DAMP LABEL <b>BIOS</b> BIOS SKYBLUE™ OR BIOS SKYBLUE™ DYNAMIC LIGHT ENGINE*** <b>MOD</b> MODIFIED LUMINAIRE (CONTACT LOCAL REP)

**SAMPLE CODE: UA1-P1EB-24-MW-WTP-LED1/27K-UNV-48-DM1**

\*Fixture will ship with one of three standard OAH's (48", 100" or 144") field adjustable to the desired height.

\*\*Contact factory for **BIOS SkyBlue®** or **BIOS SkyBlue® Dynamic** light engine and control options. Visit [ocl.com/BIOS](http://ocl.com/BIOS) for more information.

UP TO **80** LM/W

		LUMENS AND WATTAGE CHART				
		24"	36"	48"	60"	89"
<b>LED1</b>	LUMENS DELIVERED	1120	1680	2240	2800	4080
	SYSTEM WATTAGE	14	21	28	35	51
<b>LED2</b>	LUMENS DELIVERED	1680	2480	3360	4160	6160
	SYSTEM WATTAGE	21	31	42	52	77

This chart was created for a 35K color temp. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. Wattage and lumen data approx. pending LM-79 testing.

**MODS, NOTES, & COMMENTS**



This product meets the material restrictions of Article 4 of the RoHS Directive (2011/65/EU), including Commission Delegated Directive 2015/863