

Una™

PENDANT

FEATURES


- SIMPLE, LINEAR 3"W X 3.5"H PROFILE CAN BE CONNECTED TO CREATE LONG, CONTINUOUS RUNS
- FIELD REPLACEMENT OF LED ARRAYS AND DRIVERS IS SIMPLE AND REQUIRES MINIMAL EFFORT
- QUALITY CONSTRUCTION INCLUDES HEAVY GAUGE SHEET METAL, EXTRUDED ALUMINUM, DIE-CAST ALUMINUM, AND EXTRUDED ACRYLIC
- EXTRUDED DIFFUSER IS FROSTED WHITE ACRYLIC, UV STABLE AND UL-94 HB FLAME RATED
- 3 STEP COLOR BINNING



CATALOG CODES

| | | | | | | | | | |
|------------|----------------|----------|-----------|----------|--------------|------------|----------|------------|----------|
| UA1 | P1EB | C | MW | E | F | UNV | H | DM1 | J |
| SERIES | HANGING SYSTEM | SIZE | DIFFUSER | FINISH | LIGHT SOURCE | VOLTAGE | OAH | CONTROL | OPTIONS |

SPECIFY CATALOG CODE

| A | B | C | D | E | | | | | | | | | | | | |
|--|--|----------------------------------|-----------------------|---|------------------|------------------------|---------------------------|-----------------------|-------------------|----------------------------|---------------------------|----------------------|---------------------|---------------------------|-----------------------|--|
| SERIES | HANGING SYSTEM | SIZE | DIFFUSER | FINISH | | | | | | | | | | | | |
|  UA1 UNA | P1EB PENDANT WITH AN AIRCRAFT CABLE ON EACH END OF THE FIXTURE AND A POWER CORD ON ONE END | 24 36 48 60 89 XX | MW MATTE WHITE | POWDER COAT FINISHES <table border="0"> <tr> <td>BKP BLACK</td> <td>MWP MATTE WHITE</td> </tr> <tr> <td>BMP BRASS METALLIC</td> <td>SGP STEEL GRAY</td> </tr> <tr> <td>BNP BRONZE</td> <td>SMP SILVER METALLIC</td> </tr> <tr> <td>BTP BLACK TEXTURED</td> <td>SWP SKY WHITE</td> </tr> <tr> <td>GRP GRAPHITE</td> <td>WTP WHITE TEXTURED</td> </tr> <tr> <td>GLP GOLDTASTIC</td> <td></td> </tr> </table> PREMIUM METAL FINISHES BAL BRUSHED ALUMINUM | BKP BLACK | MWP MATTE WHITE | BMP BRASS METALLIC | SGP STEEL GRAY | BNP BRONZE | SMP SILVER METALLIC | BTP BLACK TEXTURED | SWP SKY WHITE | GRP GRAPHITE | WTP WHITE TEXTURED | GLP GOLDTASTIC | |
| BKP BLACK | MWP MATTE WHITE | | | | | | | | | | | | | | | |
| BMP BRASS METALLIC | SGP STEEL GRAY | | | | | | | | | | | | | | | |
| BNP BRONZE | SMP SILVER METALLIC | | | | | | | | | | | | | | | |
| BTP BLACK TEXTURED | SWP SKY WHITE | | | | | | | | | | | | | | | |
| GRP GRAPHITE | WTP WHITE TEXTURED | | | | | | | | | | | | | | | |
| GLP GOLDTASTIC | | | | | | | | | | | | | | | | |

| F | | G | H | I | J |
|-----------------------------------|---|--------------------|------------------|-----------------------------|--|
| LIGHT SOURCE | | VOLTAGE | OAH* | CONTROL | OPTIONS |
| LED OUTPUT LED1 LED2 | COLOR TEMP 27K 30K 35K 40K | UNV 120-277 | 48 100 144 | DM1 0-10V DIMMING 1% | ULD DAMP LABEL MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP) |

SAMPLE CODE: UA1-P1EB-24-MW-WTP-LED1/27K-UNV-48-DM1

*Fixture will ship with one of three standard OAH's (48", 100" or 144") field adjustable to the desired height.

UP TO **80** LM/W

LUMENS AND WATTAGE CHART

| | | 24" | 36" | 48" | 60" | 89" |
|-------------|------------------|------|------|------|------|------|
| LED1 | LUMENS DELIVERED | 1120 | 1680 | 2240 | 2800 | 4080 |
| | SYSTEM WATTAGE | 14 | 21 | 28 | 35 | 51 |
| LED2 | LUMENS DELIVERED | 1680 | 2480 | 3360 | 4160 | 6160 |
| | SYSTEM WATTAGE | 21 | 31 | 42 | 52 | 77 |

This chart was created for a 35K color temp. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. Wattage and lumen data approx. pending LM-79 testing.

MODS, NOTES, & COMMENTS



This product meets the material restrictions of Article 4 of the RoHS Directive (2011/65/EU), including Commission Delegated Directive 2015/863