



Westport™

PENDANT

FEATURES

- MODERN VERSION OF THE CLASSIC, INDUSTRIAL STYLE PENDANT
- INJECTION MOLDED PRISMATIC ACRYLIC DIFFUSER
- LASER-CUT SLOTS IN ALUMINUM FITTER ALLOW CIRCULATION TO KEEP LAMPS COOLER FOR DURABILITY AND EFFICIENCY
- UNIQUE BOTTOM DIFFUSER ELIMINATES HARSH GLARE FROM LAMPS WHILE STILL TRANSMITTING LIGHT
- CANOPY, FITTER, AND BOTTOM TRIM RING ARE SPUN FROM SOLID, NON-FERROUS 0.064" THICK ALUMINUM



CATALOG CODES

WP1	P1AA	C	D	E	F	UNV	H	DM1	J
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LIGHT SOURCE	VOLTAGE	OAH	CONTROL	OPTIONS

SPECIFY CATALOG CODE		C		D		E	
A	B	SIZE	DIFFUSER		FINISH		
 WP1 WESTPORT	P1AA PENDANT WITH A SINGLE CENTER STEM	14	CL CLEAR PRISMATIC ACRYLIC	POWDER COAT FINISHES BKP BLACK MWP MATTE WHITE BMP BRASS METALLIC SGP STEEL GRAY BNP BRONZE SMP SILVER METALLIC BTP BLACK TEXTURED SWP SKY WHITE GRP GRAPHITE WTP WHITE TEXTURED GLP GOLDTASTIC			
		18	FR FROSTED PRISMATIC ACRYLIC	PREMIUM METAL FINISHES BAL BRUSHED ALUMINUM			

F		G		H		I		J	
LIGHT SOURCE		VOLTAGE		OAH		CONTROL		OPTIONS	
LED OUTPUT LED1 LED2	COLOR TEMP 27K 30K 35K 40K	UNV	120-277	SPECIFY IN INCHES		DM1	0-10V DIMMING 1%		ULD UL DAMP LABEL MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP)

SAMPLE CODE: WP1-P1AA-14-CL-WTP-LED1/27K-UNV-34-DM1

UP TO **94** LM/W

LUMENS AND WATTAGE CHART		SIZE	
		14"	18"
LED1	LUMENS DELIVERED	1750	1750
	SYSTEM WATTAGE	20	20
LED2	LUMENS DELIVERED	2350	2350
	SYSTEM WATTAGE	25	25

This chart was created for a 35K color temp. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp.

MODS, NOTES, & COMMENTS



This product meets the material restrictions of Article 4 of the RoHS Directive (2011/65/EU), including Commission Delegated Directive 2015/863