



# Zen™

CEILING / SCONCE

**FEATURES**

- MINIMAL APPEARANCE AND EXTREMELY SHALLOW 0.75" PROJECTION ALLOWS SEAMLESS INTEGRATION WITH INTERIOR DESIGN
- EASILY INCORPORATE CUSTOM DIFFUSER MATERIALS, COLORS OR PATTERNS
- STANDARD DIFFUSER IS VIRGIN WHITE ACRYLIC
- NO VISIBLE HARDWARE OR FASTENERS
- OUTER FACE IS PRECISION MITER-CUT ALUMINUM EXTRUSION
- QUALITY CONSTRUCTION INCLUDES HEAVY GAUGE SHEET METAL, EXTRUDED ALUMINUM

MADE IN USA



**CATALOG CODES**

<b>ZE1</b>	-	<b>B</b>	-	<b>C</b>	-	<b>E</b>	-	<b>f</b>	-	<b>UNV</b>	-	<b>DM1</b>	-	<b>J</b>		
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS

SPECIFY CATALOG CODE							
A	B	C	D	E			
SERIES	HANGING SYSTEM*	SIZE	DIFFUSER	FINISH			
 <b>ZE1</b> ZEN	<b>C1NB</b> RECESSED CEILING MOUNT	<b>20</b>	<b>GW</b> GLOSS WHITE ACRYLIC <b>MW</b> MATTE WHITE ACRYLIC	<b>POWDER COAT FINISHES</b> <b>BKP</b> BLACK <b>BMP</b> BRASS METALLIC <b>BNP</b> BRONZE <b>BTP</b> BLACK TEXTURED <b>GRP</b> GRAPHITE <b>GLP</b> GOLDTASTIC  <b>PREMIUM METAL FINISHES</b> <b>BAL</b> BRUSHED ALUMINUM			
		<b>S1SE</b> RECESSED INDOOR ADA COMPLIANT SCONCE  <b>NOTE: S1SE CAN BE MOUNTED HORIZONTALLY OR VERTICALLY</b>	<b>27</b>		<b>FA</b> FAUX ALABASTER ACRYLIC <b>WS</b> WHITE SWIRL ACRYLIC		
	<b>39</b>						
	<b>51</b>						
	<b>63</b>						
			F		G	H	I
<b>LIGHT SOURCE</b>		<b>VOLTAGE</b>		<b>CONTROL</b>		<b>OPTIONS</b>	
<b>LED OUTPUT</b> <b>LED1</b> <b>LED2</b>	<b>COLOR TEMP</b> <b>27K</b> <b>30K</b> <b>35K</b> <b>40K</b>	<b>UNV</b> 120-277	<b>DM1</b> 0-10V DIMMING 1%	<b>ULD</b> DAMP LABEL ( <b>S1SA</b> ONLY) <b>BIOS</b> BIOS SKYBLUE™ OR BIOS SKLYBLUE™ DYNAMIC LIGHT ENGINE* <b>MOD</b> MODIFIED LUMINAIRE (CONTACT LOCAL REP)			

SAMPLE CODE: ZE1-C1NB-27-MW-WTP-LED1/27K-UNV-DM1

\*Contact factory for BIOS SkyBlue® or BIOS SkyBlue® Dynamic light engine and control options. Visit [ocl.com/BIOS](http://ocl.com/BIOS) for more information.

**LUMENS AND WATTAGE CHART**

		20"	27"	39"	51"	63"
<b>LED1</b>	LUMENS DELIVERED	650	950	1450	2000	2500
	SYSTEM WATTAGE	10	15	25	35	40
<b>LED2</b>	LUMENS DELIVERED	800	1200	1850	2500	3150
	SYSTEM WATTAGE	15	20	30	40	55

UP TO **62** LM/W

This chart was created for a 35K color temp. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. Wattage and lumen data approx. pending LM-79 testing.

**MODS, NOTES, & COMMENTS**