



Orion™

CEILING


FEATURES

- THE ORION FEATURES A SIMPLE, SHALLOW DOME AND IS ACCENTED BY A SMALL BOTTOM FINIAL
- CONSTRUCTED WITH SOLID, NON-FERROUS BRASS OR ALUMINUM
- THERMALLY FORMED ACRYLIC RANGES FROM 3/16" TO 1/4" THICK, DEPENDING ON SIZE. VIRGIN WHITE ACRYLIC IS UV STABLE, AND ALL FAUX ACRYLIC COLORS ARE MIXED COMPLETELY THROUGH TO AVOID NOTICEABLE FADING
- WHITE ACRYLIC IS UL-94 HB FLAME CLASS RATING
- OCL METAL FINISHES ARE APPLIED BY HAND AND RECEIVE A PROTECTIVE CLEAR COAT



CATALOG CODES

ON1	-	C1NA	-	C	-	D	-	E	-	F	-	UNV	-	DM1	-	I
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS

SPECIFY CATALOG CODE		A	B	C	D	E		
		SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH		
 ON1 ORION	C1NA	SURFACE CEILING MOUNT	16	GW GLOSS WHITE ACRYLIC	POWDER COAT FINISHES		PREMIUM METAL FINISHES	
			19	PREMIUM ACRYLIC	BKP BLACK	PAL POLISHED ALUMINUM		
			23	MW MATTE WHITE ACRYLIC FA FAUX ALABASTER ACRYLIC WS WHITE SWIRL ACRYLIC	BMP BRASS METALLIC	BAL BRUSHED ALUMINUM		
					BNP BRONZE	PTR PEWTER		
					BTP BLACK TEXTURED	PBR POLISHED BRASS		
					GRP GRAPHITE	BBR BRUSHED BRASS		
					GLP GOLDTASTIC	ABR ANTIQUE BRASS		
					MWP MATTE WHITE	STB STATUARY BRONZE		
					SGP STEEL GRAY	SNK SATIN NICKEL		
					SMP SILVER METALLIC	ORB OIL RUBBED BRONZE		
					SWP SKY WHITE			
					WTP WHITE TEXTURED			

F		G	H	I
LIGHT SOURCE		VOLTAGE	CONTROL	OPTIONS
LED OUTPUT LED1	COLOR TEMP 27K 30K 35K 40K	UNV 120-277	DM1 0-10V DIMMING 1%	MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP)

SAMPLE CODE: ON1-C1NA-16-MW-BAL-LED1/35K-UNV-DM1

LUMENS AND WATTAGE CHART		16	19	23
LED1	LUMENS DELIVERED	1250	1250	1250
	SYSTEM WATTAGE	25	25	25

This chart was created for a 35K color temp with standard white acrylic. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. LED wattage and lumen data approx. pending LM-79 testing.

MODS, NOTES, & COMMENTS