



Orion™

PENDANT

FEATURES


- THE SIMPLE, SHALLOW DOME OF THE ORION IS ACCENTED BY TRIPOD HANGING SYSTEMS
- CONSTRUCTED WITH SOLID, NON-FERROUS BRASS OR ALUMINUM
- THERMALLY FORMED ACRYLIC RANGES FROM 3/16" TO 1/4" THICK, DEPENDING ON SIZE. VIRGIN WHITE ACRYLIC IS UV STABLE, AND ALL FAUX ACRYLIC COLORS ARE MIXED COMPLETELY THROUGH TO AVOID NOTICEABLE FADING
- WHITE ACRYLIC IS UL-94 HB FLAME CLASS RATING
- OCL METAL FINISHES ARE APPLIED BY HAND AND RECEIVE A PROTECTIVE CLEAR COAT



CATALOG CODES

ON1	-	B	-	C	-	E	-	F	-	H	-	I	-	J				
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		OAH		CONTROL		OPTIONS

SPECIFY CATALOG CODE

A	B	C	D	E
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH
 ON1 ORION	PIAA PENDANT WITH A SINGLE CENTER STEM	23	GW GLOSS WHITE ACRYLIC	POWDER COAT FINISHES BKP BLACK BMP BRASS METALLIC BNP BRONZE BTP BLACK TEXTURED GRP GRAPHITE GLP GOLDTASTIC MWP MATTE WHITE SGP STEEL GRAY SMP SILVER METALLIC SWP SKY WHITE WTP WHITE TEXTURED
	PIAH PENDANT WITH 3 ANGLED STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY	30	PREMIUM ACRYLIC	
	PIAI PENDANT WITH 3 ANGLED REEDED STEMS TO COLLECTOR AND A SINGLE REEDED CENTER STEM FROM TRIM RING TO CANOPY	36	FA FAUX ALABASTER ACRYLIC	
	PIED PENDANT WITH 3 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY	42	WS WHITE SWIRL ACRYLIC	
				PREMIUM METAL FINISHES PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM PTR PEWTER PBR POLISHED BRASS BBR BRUSHED BRASS ABR ANTIQUE BRASS STB STATUARY BRONZE SNK SATIN NICKEL ORB OIL RUBBED BRONZE

F	G	H	I	J
LIGHT SOURCE	VOLTAGE	OAH	CONTROL	OPTIONS
LED OUTPUT LED1 LED2 NOTE: TOP LENS STANDARD IN LED	COLOR TEMP 27K 30K 35K 40K	UNV 120-277	SPECIFY IN INCHES	DM1 0-10V DIMMING 1% MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP)
SCREW IN OUTPUT 3INI50 3 - E26 MEDIUM BASE SOCKET - A19 LAMP (23") 150W MAX INC PER LAMP (BY OTHERS) 6INI50 6 - E26 MEDIUM BASE SOCKET - A19 LAMP (30", 36") 150W MAX INC PER LAMP (BY OTHERS) 8INI50 8 - E26 MEDIUM BASE SOCKET - A19 LAMP (42") 150W MAX INC PER LAMP (BY OTHERS)	LEAVE BLANK FOR SCREW IN	120V (SCREW IN ONLY)	LEAVE BLANK FOR SCREW IN	

SAMPLE CODE: ON1-P1AA-23-GW-BAL-LED1/30K-UNV-48-DM1

MODS, NOTES, & COMMENTS

LUMENS AND WATTAGE CHART		23	30	36	42
LED1	LUMENS DELIVERED	4500	4500	4500	4500
	SYSTEM WATTAGE	50	50	50	50
LED2	LUMENS DELIVERED	9100	9100	9100	9100
	SYSTEM WATTAGE	105	105	105	105

This chart was created for a 35K color temp with standard white acrylic. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. LED wattage and lumen data approx. pending LM-79 testing.