



Orion™

SCENCE

FEATURES

- THE SIMPLE DOME OF THE ORION EMITS A SOFT GLOW
- ITS MINIMAL DESIGN MAKES IT A WELCOME PIECE FOR BOTH CONTEMPORARY AND TRADITIONAL APPLICATIONS
- THERMALLY FORMED ACRYLIC RANGES FROM 3/16" TO 1/4" THICK, DEPENDING ON SIZE. VIRGIN WHITE ACRYLIC IS UV STABLE, AND ALL FAUX ACRYLIC COLORS ARE MIXED COMPLETELY THROUGH TO AVOID NOTICEABLE FADING
- WHITE ACRYLIC IS UL-94 HB FLAME CLASS RATING



CATALOG CODES

ON1	-	S1SA	-	C	-	D	-	NFA	-	F	-	G	-	H	-	I
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS

SPECIFY CATALOG CODE

A	B	C	D	E
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH
 ON1 ORION	S1SA INDOOR ADA COMPLIANT SCENCE	13 16	GW GLOSS WHITE ACRYLIC PREMIUM ACRYLIC MW MATTE WHITE ACRYLIC FA FAUX ALABASTER ACRYLIC WS WHITE SWIRL ACRYLIC	NFA NO FINISH AVAILABLE

F	G	H	I
LIGHT SOURCE	VOLTAGE	CONTROL	OPTIONS
LED OUTPUT LED1 NOTE: TOP LENS STANDARD IN LED	COLOR TEMP 27K 30K 35K 40K	UNV 120-277	DM1 0-10V DIMMING 1% MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP)
SCREW IN OUTPUT 2IN40 2 - E12 BASE SOCKET - B10 LAMP 40W MAX INC PER LAMP (BY OTHERS)	LEAVE BLANK FOR SCREW IN	120V (SCREW IN ONLY)	LEAVE BLANK FOR SCREW IN

SAMPLE CODE: ON1-S1SA-13-MW-NFA-LED1/27K-UNV-DM1

MODS, NOTES, & COMMENTS

LUMENS AND WATTAGE CHART		13	16
LED1	LUMENS DELIVERED	1125	1125
	SYSTEM WATTAGE	15	15

This chart was created for a 35K color temp with standard white acrylic. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. LED wattage and lumen data approx. pending LM-79 testing.