



Reflection™

CEILING


FEATURES

- THE REFLECTION FEATURES TWO ELEGANT TRIM RINGS THROUGH WHICH THERE IS A SOFT GLOW OF LIGHT
- CONSTRUCTED WITH SOLID, NON-FERROUS BRASS OR ALUMINUM
- THERMALLY FORMED ACRYLIC RANGES FROM 3/16" TO 1/4" THICK, DEPENDING ON SIZE. VIRGIN WHITE ACRYLIC IS UV STABLE, AND ALL FAUX ACRYLIC COLORS ARE MIXED COMPLETELY THROUGH TO AVOID NOTICEABLE FADING
- WHITE ACRYLIC IS UL-94 HB FLAME CLASS RATING
- OCL METAL FINISHES ARE APPLIED BY HAND AND RECEIVE A PROTECTIVE CLEAR COAT



CATALOG CODES

RF1	-	C1NA	-	C	-	D	-	E	-	F	-	G	-	H	-	I
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS

SPECIFY CATALOG CODE		A	B	C	D	E		F	G	H	I
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH		LIGHT SOURCE	VOLTAGE	CONTROL	OPTIONS		
 RF1 REFLECTION	C1NA SURFACE CEILING MOUNT	16	GW GLOSS WHITE ACRYLIC	POWDER COAT FINISHES		LED1 LED OUTPUT	UNV 120-277	DM1 0-10V DIMMING 1%	MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP)		
		26	PREMIUM ACRYLIC MW MATTE WHITE ACRYLIC	PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM PTR PEWTER PBR POLISHED BRASS BBR BRUSHED BRASS ABR ANTIQUE BRASS STB STATUARY BRONZE SNK SATIN NICKEL ORB OIL RUBBED BRONZE							
2IN60 2 - E26 MEDIUM BASE SOCKET - A19 LAMP (16") 60W MAX INC PER LAMP (BY OTHERS)	LEAVE BLANK FOR SCREW IN	120V (SCREW IN ONLY)	LEAVE BLANK FOR SCREW IN								
2IN100 2 - E26 MEDIUM BASE SOCKET - A19 LAMP (26") 100W MAX INC PER LAMP (BY OTHERS)											
SAMPLE CODE: RF1-C1NA-16-MW-BAL-LED1/35K-UNV-DM1											

MODS, NOTES, & COMMENTS

LUMENS AND WATTAGE CHART		16	26
LED1	LUMENS DELIVERED	1250	1250
	SYSTEM WATTAGE	25	25

This chart was created for a 35K color temp with standard white acrylic. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. LED wattage and lumen data approx. pending LM-79 testing.