



Reflection™

PENDANT

FEATURES

- THE REFLECTION PENDANT FEATURES TWO ELEGANT TRIM RINGS THROUGH WHICH THERE IS A SOFT GLOW OF LIGHT
- CONSTRUCTED WITH SOLID, NON-FERROUS BRASS OR ALUMINUM
- THERMALLY FORMED ACRYLIC RANGES FROM 3/16" TO 1/4" THICK, DEPENDING ON SIZE. VIRGIN WHITE ACRYLIC IS UV STABLE, AND ALL FAUX ACRYLIC COLORS ARE MIXED COMPLETELY THROUGH TO AVOID NOTICEABLE FADING
- WHITE ACRYLIC IS UL-94 HB FLAME CLASS RATING
- OCL METAL FINISHES ARE APPLIED BY HAND AND RECEIVE A PROTECTIVE CLEAR COAT



CATALOG CODES

RF1	-	P1ED	-	C	-	E	-	F	-	H	-	I	-	J		
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		VOLTAGE		OAH		CONTROL		OPTIONS

SPECIFY CATALOG CODE

A	B	C	D	E	
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	
<p>RF1 REFLECTION</p>	P1ED PENDANT WITH 3 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY	26	GW GLOSS WHITE ACRYLIC	POWDER COAT FINISHES BKP BLACK BMP BRASS METALLIC BNP BRONZE BTP BLACK TEXTURED GRP GRAPHITE GLP GOLDTASTIC MWP MATTE WHITE SGP STEEL GRAY SMP SILVER METALLIC SWP SKY WHITE WTP WHITE TEXTURED	
		33	PREMIUM ACRYLIC		PREMIUM METAL FINISHES PAL POLISHED ALUMINUM BAL BRUSHED ALUMINUM PTR PEWTER PBR POLISHED BRASS BBR BRUSHED BRASS ABR ANTIQUE BRASS STB STATUARY BRONZE SNK SATIN NICKEL ORB OIL RUBBED BRONZE
		41	MW MATTE WHITE ACRYLIC		
			FA FAUX ALABASTER ACRYLIC		
		WS WHITE SWIRL ACRYLIC			

F	G	H	I	J
LIGHT SOURCE	VOLTAGE	OAH	CONTROL	OPTIONS
LED OUTPUT LED1 LED2 NOTE: TOP LENS STANDARD IN LED	COLOR TEMP 27K 30K 35K 40K	UNV 120-277	SPECIFY IN INCHES	DM1 0-10V DIMMING 1% LEAVE BLANK FOR SCREW IN
3IN150 3 - E26 MEDIUM BASE SOCKET - A19 LAMP (26") 150W MAX INC PER LAMP (BY OTHERS) 6IN150 6 - E26 MEDIUM BASE SOCKET - A19 LAMP (33") 150W MAX INC PER LAMP (BY OTHERS) 8IN150 8 - E26 MEDIUM BASE SOCKET - A19 LAMP (41") 150W MAX INC PER LAMP (BY OTHERS)	LEAVE BLANK FOR SCREW IN	120V (SCREW IN ONLY)		

SAMPLE CODE: RF1-P1ED-26-GW-BAL-LED1-27K-UNV-48-DM1

LUMENS AND WATTAGE CHART		26	33	41
LED1	LUMENS DELIVERED	4500	4500	4500
	SYSTEM WATTAGE	50	50	50
LED2	LUMENS DELIVERED	9100	9100	9100
	SYSTEM WATTAGE	105	105	105

MODS, NOTES, & COMMENTS

This chart was created for a 35K color temp with standard white acrylic. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. LED wattage and lumen data approx. pending LM-79 testing.