



Stellar™

PENDANT

FEATURES

- THE CLASSIC LOOK OF CROWN MOLDING CREATES THE STATELY APPEARANCE OF THE STELLAR
- CONSTRUCTED WITH SOLID, NON-FERROUS BRASS OR ALUMINUM
- THERMALLY FORMED ACRYLIC RANGES FROM 3/16" TO 1/4" THICK, DEPENDING ON SIZE. VIRGIN WHITE ACRYLIC IS UV STABLE, AND ALL FAUX ACRYLIC COLORS ARE MIXED COMPLETELY THROUGH TO AVOID NOTICEABLE FADING
- WHITE ACRYLIC IS UL-94 HB FLAME CLASS RATING
- OCL METAL FINISHES ARE APPLIED BY HAND AND RECEIVE A PROTECTIVE CLEAR COAT



CATALOG CODES

A	B	C	D	E	F	G	H	I	J
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LIGHT SOURCE	VOLTAGE	OAH	CONTROL	OPTIONS

SPECIFY CATALOG CODE

A	B	C	D	E
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH
<p>ST1 STELLAR (SHALLOW DIFFUSER)</p> <p>ST2 STELLAR (DEEP DIFFUSER)</p>	<p>PIAA PENDANT WITH A SINGLE CENTER STEM</p> <p>PIAH PENDANT WITH 3 ANGLED STEMS TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY</p> <p>PIAI PENDANT WITH 3 ANGLED REEDED STEMS TO COLLECTOR AND A SINGLE REEDED CENTER STEM FROM TRIM RING TO CANOPY AND CAST BRASS SHELL ACCENTS (SEE RIGHT)</p> <p>PIAI</p> <p>PIED PENDANT WITH 3 ANGLED AIRCRAFT CABLES TO COLLECTOR AND A SINGLE CENTER STEM FROM TRIM RING TO CANOPY</p>	<p>24</p> <p>31</p> <p>42</p>	<p>GW GLOSS WHITE ACRYLIC</p> <p>PREMIUM ACRYLIC</p> <p>MW MATTE WHITE ACRYLIC</p> <p>FA FAUX ALABASTER ACRYLIC</p> <p>WS WHITE SWIRL ACRYLIC</p>	<p>POWDER COAT FINISHES</p> <p>BKP BLACK</p> <p>BMP BRASS METALLIC</p> <p>BNP BRONZE</p> <p>BTP BLACK TEXTURED</p> <p>GRP GRAPHITE</p> <p>GLP GOLDTASTIC</p> <p>MWP MATTE WHITE</p> <p>SGP STEEL GRAY</p> <p>SMP SILVER METALLIC</p> <p>SWP SKY WHITE</p> <p>WTP WHITE TEXTURED</p> <p>PREMIUM METAL FINISHES</p> <p>PAL POLISHED ALUMINUM</p> <p>BAL BRUSHED ALUMINUM</p> <p>PTR PEWTER</p> <p>PBR POLISHED BRASS</p> <p>BBR BRUSHED BRASS</p> <p>ABR ANTIQUE BRASS</p> <p>STB STATUARY BRONZE</p> <p>SNK SATIN NICKEL</p> <p>ORB OIL RUBBED BRONZE</p>

F	G	H	I	J
LIGHT SOURCE	VOLTAGE	OAH	CONTROL	OPTIONS
<p>LED OUTPUT</p> <p>LED1</p> <p>LED2</p> <p>NOTE: TOP LENS STANDARD IN LED</p>	<p>COLOR TEMP</p> <p>27K</p> <p>30K</p> <p>35K</p> <p>40K</p>	<p>UNV 120-277</p>	<p>SPECIFY IN INCHES</p> <p>DMI 0-10V DIMMING 1%</p>	<p>CIB CLEAR INNER BOWL</p> <p>VOL "V" STYLE OVERLAY AND BOTTOM FINIAL (SEE RIGHT)</p> <p>MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP)</p> <p>VOL</p>
<p>3IN150 3 - E26 MEDIUM BASE SOCKET - A19 LAMP (24", 31") 150W MAX INC PER LAMP (BY OTHERS)</p> <p>6IN150 6 - E26 MEDIUM BASE SOCKET - A19 LAMP (42") 150W MAX INC PER LAMP (BY OTHERS)</p>	<p>LEAVE BLANK FOR SCREW IN</p>	<p>120V (SCREW IN ONLY)</p>	<p>LEAVE BLANK FOR SCREW IN</p>	

SAMPLE CODE: ST1-PIAA-24-GW-BAL-LED1/30K-UNV-48-DMI

MODS, NOTES, & COMMENTS

LUMENS AND WATTAGE CHART		24	31	42
LED1	LUMENS DELIVERED	4500	4500	4500
	SYSTEM WATTAGE	50	50	50
LED2	LUMENS DELIVERED	9100	9100	9100
	SYSTEM WATTAGE	105	105	105

This chart was created for a 35K color temp with standard white acrylic. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. LED wattage and lumen data approx. pending LM-79 testing.