



# Stellar™

## SCONCE

### FEATURES

- THE CLASSIC LOOK OF CROWN MOLDING CREATES THE STately APPEARANCE OF THE STELLAR
- A TRANSITIONAL DESIGN MAKES IT A WELCOME ADDITION FOR BOTH CONTEMPORARY AND TRADITIONAL APPLICATIONS
- CONSTRUCTED WITH SOLID, NON-FERROUS BRASS OR ALUMINUM
- THERMALLY FORMED ACRYLIC RANGES FROM 3/16" TO 1/4" THICK, DEPENDING ON SIZE. VIRGIN WHITE ACRYLIC IS UV STABLE, AND ALL FAUX ACRYLIC COLORS ARE MIXED COMPLETELY THROUGH TO AVOID NOTICEABLE FADING
- WHITE ACRYLIC IS UL-94 HB FLAME CLASS RATING
- OCL METAL FINISHES ARE APPLIED BY HAND AND RECEIVE A PROTECTIVE CLEAR COAT



### CATALOG CODES

<b>ST1</b>	-	<b>S1SA</b>	-	<b>C</b>	-	<b>D</b>	-	<b>E</b>	-	<b>F</b>	-	<b>G</b>	-	<b>H</b>	-	<b>I</b>
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS

### SPECIFY CATALOG CODE

A		B		C	D		E	
SERIES	HANGING SYSTEM		SIZE	DIFFUSER		FINISH		
 <b>ST1</b> STELLAR	<b>S1SA</b>	INDOOR ADA COMPLIANT SCONCE	<b>18</b>  <b>24</b>	<b>GW</b> GLOSS WHITE ACRYLIC  <b>PREMIUM ACRYLIC</b> <b>MW</b> MATTE WHITE ACRYLIC <b>FA</b> FAUX ALABASTER ACRYLIC <b>WS</b> WHITE SWIRL ACRYLIC	<b>POWDER COAT FINISHES</b> <b>BKP</b> BLACK <b>BMP</b> BRASS METALLIC <b>BNP</b> BRONZE <b>BTP</b> BLACK TEXTURED <b>GRP</b> GRAPHITE <b>GLP</b> GOLDTASTIC <b>MWP</b> MATTE WHITE <b>SGP</b> STEEL GRAY <b>SMP</b> SILVER METALLIC <b>SWP</b> SKY WHITE <b>WTP</b> WHITE TEXTURED	<b>PREMIUM METAL FINISHES</b> <b>PAL</b> POLISHED ALUMINUM <b>BAL</b> BRUSHED ALUMINUM <b>PTR</b> PEWTER <b>PBR</b> POLISHED BRASS <b>BBR</b> BRUSHED BRASS <b>ABR</b> ANTIQUE BRASS <b>STB</b> STATUARY BRONZE <b>SNK</b> SATIN NICKEL <b>ORB</b> OIL RUBBED BRONZE		

F		G		H		I	
LIGHT SOURCE		VOLTAGE		CONTROL		OPTIONS	
<b>LED OUTPUT LED1</b>  <b>NOTE:</b> TOP LENS STANDARD IN LED	<b>COLOR TEMP</b> 27K 30K 35K 40K	<b>UNV</b> 120-277	<b>DMI</b> 0-10V DIMMING 1%	<b>CBS</b> CAST BRASS SHELL ACCENT (SEE RIGHT) <b>MOD</b> MODIFIED LUMINAIRE (CONTACT LOCAL REP)	 <b>CBS</b>		
<b>2IN40</b> 2 - E12 BASE SOCKET - B10 LAMP 40W MAX INC PER LAMP (BY OTHERS)	<b>LEAVE BLANK FOR SCREW IN</b>	<b>120V</b> (SCREW IN ONLY)	<b>LEAVE BLANK FOR SCREW IN</b>				

SAMPLE CODE: ST1-S1SA-24-MW-ABR-LED1/27K-UNV-DMI

### MODS, NOTES, & COMMENTS

LUMENS AND WATTAGE CHART		18	24
<b>LED1</b>	LUMENS DELIVERED	1125	1125
	SYSTEM WATTAGE	15	15

This chart was created for a 35K color temp with standard white acrylic. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. LED wattage and lumen data approx. pending LM-79 testing.