


Centro™ Pendant | Ceiling | Sconce

ESSENTIALS SPEC SHEET

CATALOG CODES

CT1	B	14	MW	E	/	UNV	H	DM1	ESS
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LIGHT SOURCE	VOLTAGE	OAH	CONTROL	OPTIONS

SPECIFY CATALOG CODE

A	B	C	D	E
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH
 CT1 CENTRO	PICF PENDANT WITH SURFACE MOUNT CANOPY, SINGLE SILVER POWER CORD; MOUNTS TO 4X4 OCTAGON J-BOX (BY OTHERS) CINA SURFACE CEILING MOUNT SISA INDOOR ADA COMPLIANT SCONCE	14	MW MATTE WHITE	POWDER COAT FINISHES BKP BLACK MWP MATTE WHITE

F			G	H	I	J
LIGHT SOURCE			VOLTAGE	OAH*	CONTROL	OPTIONS
LED OUTPUT LED1 LED2	COLOR TEMP (80+ CRI) 30K 35K 40K	COLOR TEMP (90+ CRI) 930K 935K 940K	UNV 120-277	48 100 144 LEAVE BLANK FOR CINA & SISA	DM1 0-10V DIMMING 1%	ESS ESSENTIALS

SAMPLE CODE: GL1-PIEM-36-MW-NFA-LED1/935K-UNV-48-DM1-ESS

*For Minimum OAH, see hanging systems details. Fixture will ship with one of three standard OAH's (48", 100" or 144") field adjustable to the desired height. Leave blank for **CINA** or **SISA**.


NOTES / COMMENTS

Declare.



Please note that any additional colors, sizes, and/or options are not eligible for OCL Essentials. Refer to full product specification sheet for full luminaire configuration options and detailed product specifications.

The drawings and specifications and ideas, designs and arrangements represented on these drawings are and shall remain the property of The Original Cast Lighting (OCL Architectural Lighting) and no part thereof shall be copied, disclosed, to others or used in conjunction with any work or project other than the specified project for which they have been prepared and developed, without written consent of OCL. Visual contact with these plans or specifications shall constitute conclusive evidence of acceptance of these restrictions. All specifications and information subject to change without notice.



CLICK OR SCAN FOR PRODUCT PAGE