


Glowring™ Pendant


ESSENTIALS SPEC SHEET



CATALOG CODES

GL1	B	C	MW	E	LED1 /	UNV	H	DM1	ESS
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LIGHT SOURCE	VOLTAGE	OAH	CONTROL	OPTIONS

SPECIFY CATALOG CODE

A	B	C	D	E
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH
 GL1 GLOWRING	PIEM PENDANT WITH VERTICAL AIRCRAFT CABLES TO SEPARATE MOUNTING POINTS AND POWER CORD TO CANOPY (REMOTE DRIVER)	24 36 48	MW MATTE WHITE	POWDER COAT FINISHES NFA NO FINISH AVAILABLE (GL1 WITH PIEM ONLY) BKP BLACK MWP MATTE WHITE
	P1DA PENDANT WITH VERTICAL AIRCRAFT CABLES TO SEPARATE MOUNTING POINTS AND POWER CORD TO CANOPY WITH INTEGRAL DRIVER			
	PIEC PENDANT WITH ANGLED AIRCRAFT CABLES AND POWER CORD TO CANOPY (REMOTE DRIVER)			
	P1DB PENDANT WITH ANGLED AIRCRAFT CABLES AND POWER CORD TO CANOPY WITH INTEGRAL DRIVER			

F			G	H	I	J
LIGHT SOURCE			VOLTAGE	OAH*	CONTROL	OPTIONS
LED OUTPUT LED1	COLOR TEMP (80+ CRI)	COLOR TEMP (90+ CRI)	UNV 120-277	48 100 144	DM1 0-10V DIMMING 1%	ESS ESSENTIALS
	30K	930K				
	35K	935K				
	40K	940K				

SAMPLE CODE: GL1-PIEM-36-MW-NFA-LED1/935K-UNV-48-DM1-ESS

*For Minimum OAH, see hanging systems details. Fixture will ship with one of three standard OAH's (48", 100" or 144") field adjustable to the desired height.

Fixtures with **PIEM** hanging system, canopy will be **MWP** unless specified; fixtures with **P1DA**, **PIEC** or **P1DB** hanging system, canopy will match finish choice; power cord white unless specified.

NOTES / COMMENTS

Declare.



Please note that any additional colors, sizes, and/or options are not eligible for OCL Essentials. Refer to full product specification sheet for full luminaire configuration options and detailed product specifications.

The drawings and specifications and ideas, designs and arrangements represented on these drawings are and shall remain the property of The Original Cast Lighting (OCL Architectural Lighting) and no part thereof shall be copied, disclosed, to others or used in conjunction with any work or project other than the specified project for which they have been prepared and developed, without written consent of OCL. Visual contact with these plans or specifications shall constitute conclusive evidence of acceptance of these restrictions. All specifications and information subject to change without notice.



CLICK OR SCAN FOR PRODUCT PAGE