



CLICK OR SCAN FOR PRODUCT PAGE

PROJECT NAME: \_\_\_\_\_ TYPE: \_\_\_\_\_

QTY: \_\_\_\_\_


# Nova™ Pendant

## ESSENTIALS SPEC SHEET

### CATALOG CODES

<b>NO1</b>	<b>B</b>	<b>C</b>	<b>MW</b>	<b>E</b>	<b>/</b>	<b>UNV</b>	<b>H</b>	<b>DM1</b>	<b>ESS</b>
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	FINISH	LIGHT SOURCE	VOLTAGE	OAH	CONTROL	OPTIONS

### SPECIFY CATALOG CODE

A	B	C	D	E
SERIES	HANGING SYSTEM	SIZE	DIFFUSER	OUTER FINISH/INNER FINISH*
 <b>NO1</b> NOVA	<b>PIFA</b> PENDANT WITH SURFACE MOUNT CANOPY, SINGLE CENTER AIRCRAFT CABLE AND SILVER POWER CORD; MOUNTS TO 4X4 OCTAGON J-BOX (BY OTHERS)	<b>18</b> <b>24</b> <b>36</b>	<b>MW</b> MATTE WHITE	<b>POWDER COAT FINISHES</b> <b>BKP</b> BLACK <b>MWP</b> MATTE WHITE <b>BMP</b> BRASS METALIC <b>GLP</b> GOLDTASTIC
	<b>PIFB</b> PENDANT WITH FLAT CANOPY, SINGLE CENTER AIRCRAFT CABLE AND SILVER POWER CORD; MOUNTS TO OCL RECESSED J-BOX (PROVIDED BY OCL)			NOTE: <b>BMP &amp; GLP</b> ARE FOR INNER COLOR ONLY

F			G	H	I	J
LIGHT SOURCE			VOLTAGE	OAH**	CONTROL	OPTIONS
<b>LED OUTPUT</b>	<b>COLOR TEMP</b> (80+ CRI)	<b>COLOR TEMP</b> (90+ CRI)	<b>UNV</b> 120-277	<b>48</b>	<b>DM1</b> 0-10V DIMMING 1%	<b>ESS</b> ESSENTIALS
<b>LED1</b>	<b>30K</b>	<b>930K</b>		<b>100</b>		
<b>LED2</b>	<b>35K</b>	<b>935K</b>		<b>144</b>		
<b>LED3</b>	<b>40K</b>	<b>940K</b>				

SAMPLE CODE: G11-PIEM-36-MW-NFA-LED1/935K-UNV-48-DM1-ESS

\* Metal shade is available with an second color on the inside surface; choose the same finish for outer and inner for single tone; **PIFA** canopy color will match the outer finish choice; **PIFB** canopy color is **MWP**

\*\*For Minimum OAH, see hanging systems details. Fixture will ship with one of three standard OAH's (48", 100" or 144") field adjustable to the desired height.

### NOTES / COMMENTS

Declare.



Please note that any additional colors, sizes, and/or options are not eligible for OCL Essentials. Refer to full product specification sheet for full luminaire configuration options and detailed product specifications.

The drawings and specifications and ideas, designs and arrangements represented on these drawings are and shall remain the property of The Original Cast Lighting (OCL Architectural Lighting) and no part thereof shall be copied, disclosed, to others or used in conjunction with any work or project other than the specified project for which they have been prepared and developed, without written consent of OCL. Visual contact with these plans or specifications shall constitute conclusive evidence of acceptance of these restrictions. All specifications and information subject to change without notice.