OCL ARCHITECTURAL LIGHTING

PROJECT NAME: _____ TYPE: _____

QTY: _____

Glowball™

PENDANT

TUNABLE WHITE OPTION AVAILABLE

RGBW OPTION AVAILABLE

FEATURES

- **AVAILABLE WITH TUNABLE WHITE AND RGBW LIGHT SOURCES**
- ELEGANT & CONTEMPORARY SPHERE WITH ROBUST FROSTED SILICONE DIFFUSER
- FIXTURES CAN BE CLUSTERED TOGETHER TO CREATE LARGE SCALE INSTALLATIONS
- DIE-CAST ALUMINUM BODY
- FIELD REPLACEABLE LEDS AND DRIVERS



CATALOG CODES

GB1	-	B	-	04	-	FS	-	E	-	F	-	UNV	-	H	-	I	-	J
SERIES		HANGING SYSTEM		SIZE		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		OAH		CONTROL		OPTIONS

SPECIFY CATALOG CODE

A — SERIES

GB1 GLOWBALL

B — HANGING SYSTEM

P1CF PENDANT WITH 5.75" SURFACE MOUNT CANOPY, SINGLE SILVER POWER CORD; MOUNTS TO 4X4 OCTAGON J-BOX (BY OTHERS)

P1FE PENDANT WITH 6" FLAT CANOPY, SINGLE SILVER POWER CORD; MOUNTS TO OCL RECESSED J-BOX (PROVIDED BY OCL) **NOTE**: STATIC WHITE ONLY

P1HA PENDANT WITH 8" SURFACE MOUNT CANOPY, SINGLE BLACK POWER CORD; MOUNTS TO 4X4 OCTAGON J-BOX (BY OTHERS) **NOTE:** REQUIRED FOR **TWH1** OR **RGBW** LIGHT SOURCE

P1JA PENDANT WITH 5" FLAT CANOPY, SINGLE BLACK POWER CORD; MOUNTS TO 4X4 OCTAGON J-BOX (BY OTHERS); REMOTE DRIVER ENCLOSURE **NOTE:** REQUIRED FOR **TWH1** OR **RGBW** LIGHT SOURCE

C — SIZE

04

D — DIFFUSER

FS FROSTED SILICONE

E — FINISH

POWDER COAT FINISHES

BKP	BLACK	**MWP**	MATTE WHITE
BMP	BRASS METALLIC	**SGP**	STEEL GRAY
BNP	BRONZE	**SMP**	SILVER METALLIC
BTP	BLACK TEXTURED	**SWP**	SKY WHITE
GRP	GRAPHITE	**WTP**	WHITE TEXTURED
GLP	GOLDTASTIC		

PREMIUM METAL FINISHES

BAL BRUSHED ALUMINUM

F — LIGHT SOURCE

LED OUTPUT	COLOR TEMP
LED1	**27K**
	30K
	35K
	40K
TWH1	TUNABLE WHITE 2700K - 5000K CRI 90+; R9 50+
RGBW	RGBW

G — VOLTAGE

UNV 120-277

H — OAH*

48
100
144

I — CONTROL

DM1 0-10V DIMMING 1%

DM8 DUAL 0-10V DIMMING 1%
NOTE: REQUIRES **P1HA** OR **P1JA** HANGING SYSTEM

DALI DALI TYPE 8 CONTROL SYSTEM, DIMMABLE TO 1%
NOTE: REQUIRES **P1HA** OR **P1JA** HANGING SYSTEM

DMX DMX CONTROL; DIMMABLE TO 1%
NOTE: REQUIRES **P1HA** OR **P1JA** HANGING SYSTEM

J — OPTIONS

ULD UL DAMP LABEL

MOD MODIFIED LUMINAIRE (CONTACT LOCAL REP)

SAMPLE CODE: GB1-P1CF-04-FS-BTP-LED1/35K-UNV-44-DM1

* For Minimum OAH, see hanging systems details. Fixture will ship with one of three standard OAH's (48", 100" or 144") field adjustable to the desired height.

MODS, NOTES, & COMMENTS

UP TO 99 LM/W

		04
LED1	LUMENS DELIVERED	790
	SYSTEM WATTAGE	8
TWH1	LUMENS DELIVERED	600
	SYSTEM WATTAGE	5
RGBW	LUMENS DELIVERED	600
	SYSTEM WATTAGE	5

This chart was created for a 35K color temp. Multiply by 0.95 for 27k color temp, 0.97 for 30k color temp, and 1.03 for 40k color temp. Wattage and lumen data for **TWH1** and **RGBW** approx. pending LM-79 testing.