OCL ARCHITECTURAL LIGHTING


[] OCL

Expanding the Boundaries of Light



EVERYONE CAN HEAR YOU, NOW

Lack of sound privacy is the biggest frustration we have with our cubicles.



The **WHY** of Acoustic Lighting

1. Open spaces and materials used:

- Increased noise levels
- Need for privacy
- Ability to concentrate

2. Decorative purposes:

- Human-centered designs
- Design flexibility
- "Palatable" option

3. Time/Cost:

- Remodeling cost vs "face lift"
- Easy to change/update
- Minimal time and effort for short-term occupancy
- Installed by one contractor

SZ

LUTIO

0

ഗ

 \overline{O}

Ч С


0

C

4


 \mathbf{O}

 \bigcirc



Make changes in construction materials used or appearance

- 1. increase wall mass and thickness
- 2. cavity partitions
- 3. studs in staggered manner
- 4. isolation blankets...
- 5. smaller window size or thicker glass
- 6. solid doors
- 7. use acoustic products that are floor mounted, wall mounted, suspended or free standing, drapery




4

Make changes in appearance:

- 1. Plants in space
- 2. Green walls



4. Lighting Fixtures




WELLTM Building Applications


 All of OCL's Acoustic luminaires when paired with BIOS can contribute to meeting WELL[™] V2 Features L03, L04, L07 and S04



Top 5 wants in an office space to increase productivity and creativity of its occupants



Natural Lighting
Indoor Plants
Quiet Working Space
Sea or Landscape
Bright Colors








ACOUSTIC LIGHTING SOLUTIONS

Photometric & Acoustic Testing

Available at ocl.com




ACOUSTIC LIGHTING SOLUTIONS

Photometric Data

Available at ocl.com

Photometric Performance





Calculation Results Illuminance 29 fc

Power Density 0.52 W/ft² Quantity 6

Spacing Results

 Spacing
 10 x 6.6 ft

 Arrangement
 2 x 3

 Offset X
 4.02 ft

 Offset Y
 2.42 ft

Room Summary

Length 20 ft Width 20 ft Height 12 ft Workplane 2.5 ft Reflectances Ceiling 80 % Walls 50 % Floor 20 %



Calculation Results


Illuminance 31 fc Power Density 0.52 W/ft² Quantity 6

Spacing Results

Spacing	10 x 6.6	f
Arrangement	2 x 3	
Offset X	4.02 ft	
Offset Y	2.42 ft	

Room Summary


Length	20	ft
Width	20	ft
Height	12	ft
Workplane	2.5	ft
Reflectances		
Ceiling	80	%
Walls	50	%
Floor	20	%



ACOUSTIC LIGHTING SOLUTIONS

Acoustic Testing

Available at ocl.com



Acoustic Test Data

1/3 Octave Center Frequency	Total Absorption		Absorption per Unit	
(Hz)	(m ²)	(Sabins)	(m ² /Unit)	(Sabins / Unit
100	0.27	2.96	0.07	0.74
** 125	-0.09	-0.96	-0.02	-0.24
160	0.53	5.67	0.13	1.42
200	0.99	10.61	0.25	2.65
** 250	1.15	12.38	0.29	3.09
315	1.76	18.92	0.44	4.73
400	2.14	23.07	0.54	5.77
** 500	2.97	31.99	0.74	8.00
630	3.44	37.01	0.86	9.25
800	3.86	41.52	0.96	10.38
** 1000	4.30	46.30	1.08	11.57
1250	4.40	47.38	1.10	11.85
1600	4.63	49.84	1.16	12.46
** 2000	4.87	52.43	1.22	13.11
2500	5.25	56.55	1.31	14.14
3150	5.40	58.15	1.35	14.54
** 4000	5.42	58.29	1.35	14.57
5000	5.56	59.86	1.39	14.97




Acoustic Test Data

		Method 1	Method 2		
Specimen Absorption		Specimen Absorption		Apparent Abs. Coefficient	
Freq. (Hz)	Sabins	Sabins / Unit	From Coverage Area Per Unit	From Total Exposed Surface Area	
31.5	-3.92	-0.98	-0.03	-0.03	
40	6.23	1.56	0.04	0.04	
50	6.05	1.51	0.04	0.04	
63	0.61	0.15	0.00	0.00	
80	-1.00	-0.25	-0.01	-0.01	
100	2.96	0.74	0.02	0.02	
125	-0.96	-0.24	-0.01	-0.01	
160	5.67	1.42	0.04	0.04	
200	10.61	2.65	0.07	0.07	
250	12.38	3.09	0.08	0.08	
315	18.92	4.73	0.12	0.12	
400	23.07	5.77	0.15	0.15	
500	31.99	8.00	0.20	0.21	
630	37.01	9.25	0.24	0.24	
800	41.52	10.38	0.27	0.27	
1,000	46.30	11.57	0.30	0.30	
1,250	47.38	11.85	0.30	0.31	
1,600	49.84	12.46	0.32	0.33	

Acoustic Performance


KWYET ACOUSTIC PERFORMANCE (4 UNITS):



FREQUENCY (HZ)

Acoustic Simulation






SIMULATION \mathbf{O} _ \vdash ഗ COU

Product: Glowring 72" (x19) Room Type: Open Office Room Size: 35'w x 20'h x 60'd Room Materials: Concrete, drywall, glass Mounting Height: 15' AFF

	500Hz	1000 Hz	2000 Hz
 Baseline RT₆₀ 	2.39	2.56	2.03
 Target RT₆₀ 	1.3	1.3	1.3
• RT ₆₀ w/ Glowring	1.90	1.91	1.55



Sound Advice:

Architectural acoustical design is an endeavor that involves a lot of consideration. An educated, experienced, and qualified professional acoustician should lead the acoustical design of any critical listening space.

Acoustic Solutions



METALLIC POWDER COAT FINISHES:




SOLID POWDER COAT FINISHES:

SKY WHITE



MWP BKP MATTE BLACK WHITE

TEXTURED POWDER COAT FINISHES:



BTP WTP BLACK WHITE TEXTURED TEXTURED

PREMIUM METAL FINISHES:



BAL BRUSHED ALUMINUM

RAL', Pantone[°] or custom finishes are also available.

These colors are for reference only. Please be aware that colors may vary per monitor. Contact your local rep for finish samples or with any questions.

FINISH OPTIONS



ACOUSTIC COLOR OPTIONS

ACOUSTIC COLORS:






These colors are for reference only. Please be aware that colors may vary per monitor. Contact your local rep with any questions.

Request a swatch sample at ocl.com/finishes

SFM - SEAFOAM





Kwyet Sphere

- 1. 21" diameter or 33" diameter spherical shape
- 2. custom sizes & shapes available
- 3. acoustic panels field-installed
- 4. 3" diameter Tubie light engine
- 5. optional performance COB downlight



Kwyet

- 1. Three standard shapes, 36" diameter
- 2. custom sizes & shapes available
- 3. acoustic panels field-installed
- 4. 3" diameter Tubie light engine
- 5. 12" tall light engine; optional downlight



Petals Acoustic

- Sound absorbing 9mm acoustic petals
- Available in Tunable White and RGBW standard
- 24", 36", 48", 60" & 72" diameters our LARGEST acoustic luminaire available
- Acoustic Petals easily field-installed
- 1.75" x 1.75" square profile with extruded silicone diffuser
- Available in 80+ or 90+ CRI
- RoHS Compliant / Declare Certified (pending)



OLUTIONS ഗ \mathbf{O} OUSTI C \triangleleft 000



Stealth

- 1. 1.75" square cross section
- 2. silicone lens faces down, inside or outside
- 3. optional acoustic panel
- 4. standard RGBW and tunable white
- 5. standard squares up to 48"
- 6. custom sizes, clusters & shapes





Rev

- 1. 1.75" square cross section
- 2. lens faces inside or outside
- 3. optional acoustic panel
- 4. standard RGBW and tunable white
- 5. custom sizes & shapes available





Glowring Acoustic

- 1. Seamless one-piece molded diffuser
- 2. Fully enclosed top surface to minimize accumulation of dust and debris
- 3. Minimal luminaire cross section size
- 4. Available with metal trim on inner diameter or outer diameter



OCL ACOUSTIC SOLUTIONS

2022 Acoustic Solutions Brochure

- All of OCL's Acoustic luminaires
- Open office case study
- Acoustic testing reports
- New acoustic color palette
- o Glossary and terminology
- "Why No NRC?" by Riverbank Acoustical Laboratories

Thank You