

PRECONFIGURED SOLO SHAPES SUBMITTAL WORKSHEET

CATALOG CODES

SL1S	-	B	-	C	-	D	-	E	/	E	-	MW	-	G	-	V	-	UNV	-	J	-	K	-	L
SERIES		HANGING SYSTEM		CORD COLOR		SHAPE		SIZE 1 (LENGTH OR DIAMETER IN INCHES)		SIZE 2 (WIDTH IN INCHES)		DIFFUSER		FINISH		LIGHT SOURCE		VOLTAGE		OAH		CONTROL		OPTIONS

SPECIFY CATALOG CODE		D		F		G	
A	B	D		F	G		
SERIES	HANGING SYSTEM	SHAPE		DIFFUSER	FINISH		
SL1S SOLO	PIEM	PENDANT WITH VERTICAL AIRCRAFT CABLES TO SEPARATE MOUNTING POINTS AND POWER CORD TO CANOPY	SQM SQUARE (MITERED)	ANS 90° ANGLE (SOFT)	MW MATTE WHITE	POWDER COAT FINISHES	
			REM RECTANGLE (MITERED)			1QA 90° ARC (QUARTER CIRCLE)	BKP BLACK
	TRM TRIANGLE (MITERED)	2QR 90° DOUBLE SQUIGGLE RIGHT	BMP BRASS METALLIC				
	PEM PENTAGON (MITERED)	2QL 90° DOUBLE SQUIGGLE LEFT	BNP BRONZE				
CINA	SURFACE CEILING MOUNT	HEM HEXAGON (MITERED)	3QA 90° TRIPLE SQUIGGLE	GRP GRAPHITE	BTP BLACK TEXTURED		
		OCM OCTAGON (MITERED)	1HA 180° ARC (HALF CIRCLE)		GLP GOLDTASTIC		
		ANM 90° ANGLE (MITERED)	2HR 180° DOUBLE ARC RIGHT		MWP MATTE WHITE		
		STR STRAIGHT	2HL 180° DOUBLE ARC LEFT		SGP STEEL GRAY		
		SQS SQUARE (SOFT)	3HA 180° TRIPLE ARC		SMP SILVER METALLIC		
		RES RECTANGLE (SOFT)	RCT RACETRACK		SWP SKY WHITE		
		TRS TRIANGLE (SOFT)	ELP ELLIPSE		WTP WHITE TEXTURED		
		PES PENTAGON (SOFT)					
		HES HEXAGON (SOFT)					
		OCS OCTAGON (SOFT)					
C		E		PREMIUM METAL FINISHES			
CORD COLOR		SIZE 1 (LENGTH OR DIAMETER IN INCHES)	SIZE 2 (WIDTH IN INCHES)	BAL BRUSHED ALUMINUM			
B BLACK POWER CORD	Indicate LENGTH/DIAMETER x WIDTH for your chosen shape. Squares, rectangles, angles, racetracks and ellipses will require two dimensions (SIZE 1 & SIZE 2). Straights, angles, squiggles & arcs, and polygons will only require one dimension (SIZE 1). See Page 6 for more details on calculating your fixture size.					CUSTOM FINISHES	
W WHITE POWER CORD						RAL _____	
				OTHER _____			

H		I		J		K		L	
LIGHT SOURCE		VOLTAGE		OAH*		CONTROL		OPTIONS	
LED OUTPUT	COLOR TEMP (80+ CRI)	COLOR TEMP (90+ CRI)	UNV 120-277	48	DM1	0-10V DIMMING 1%		ULD	DAMP LABEL
LED1	27K	927K		100				BIOS	BIOS SKYBLUE™ OR BIOS SKLYBLUE™ DYNAMIC LIGHT ENGINE**
LED2	30K	930K		144				MOD	MODIFIED LUMINAIRE (CONTACT LOCAL REP)
	35K	935K		NOTE: LEAVE BLANK WITH CINA					
	40K	940K							

SAMPLE CODE: SL1S-PXXEMW-SQM-36/48-MW-WTP-LED1/35K-UNV-100-DM1

*For Minimum OAH, see hanging systems details. PIEM will ship with one of three standard OAH's (48", 100" or 144") field adjustable to the desired height. Note our minimum OAH is 8".

Declare.



MODS, NOTES, & COMMENTS